




LUBRICANTS FOR VOLVO PASSENGER CARS



Quality counts. As one of the leading factory fill specialists we supply high performance quality. Today and tomorrow. FUCHS offers also the right lubricants for Volvo.

| Product name | Description | Specifications | Approvals | FUCHS Recommendations |
|---|--|----------------------------|--------------------------------|---|
| Engine Oils | | | | |
| TITAN GT1 PRO V SAE 0W-20  | Premium Performance Engine Oil with new XTL-Technology in ground-breaking viscosity class. Specially designed for modern VOLVO vehicles, for extreme fuel-economy characteristics and reduced CO ₂ emissions. Excellent cold starting behaviour, very fast oil circulation and outstanding performance reserves. | – | VOLVO VCC RBS0-2AE | ACEA A1/B1 |
| TITAN GT1 FLEX 5 SAE 0W-20  | Premium Performance Engine Oil with new XTL®-Technology in path-breaking viscosity class. Specially designed for highly stressed downsized engines with maximum power output, for extreme fuel-economy characteristics and reduced CO ₂ emissions. Excellent cold starting behaviour, very fast oil circulation and outstanding performance reserves. | ACEA C5 | – | VOLVO VCC RBS0-2AE |
| TITAN Supersyn FE SAE 0W-30 | Ultra High Performance, fuel-economy engine oil for a variety of vehicles with or without extended service intervals. Excellent cold starting properties and low oil consumption. | ACEA A5/B5 | VOLVO VCC 95200377 | – |
| TITAN Supersyn SAE 5W-30 | Ultra High Performance, extreme fuel-economy engine oil for a variety of vehicles with or without extended service intervals. Optimum cold starting and lower oil consumption. | ACEA A3/B4 | – | – |
| TITAN Supersyn SAE 5W-40 | Ultra High Performance, fuel-economy engine oil for a variety of vehicles with or without extended service intervals. Optimum cold starting and lower oil consumption. | ACEA A3/B4 | – | – |
| Gear Oils | | | | |
| TITAN SINTOFLUID SAE 75W-80 | Premium Performance Manual Transmission Fluid for passenger cars. Offering good gearbox efficiency. Suitable as fill for life fluid according to manufacturer. | API GL-5 | – | VOLVO 97308 |
| TITAN SINTOPOID FE SAE 75W-85  | Premium Performance fuel-economy passenger car axle fluid offering increased gearbox efficiency in passenger cars due to low viscosity level. Reduces fuel consumption and offers best properties at low temperature. Suitable as fill for life fluid according to manufacturer. | API GL-5 | – | – |
| TITAN SINTOPOID LS SAE 75W-90 | Premium Performance, fully-synthetic multifunctional gear oil, formulated with fully-synthetic base oils. Suitable for axles and transfer gear-boxes with or without self-locking differentials and also as trouble shooter for conventional manual transmissions. | API GL-4/-5/-5 incl. LS | – | – |
| TITAN SUPERGEAR MC SAE 80W-90 | Super High Performance Gear Oil based on MC-Synthesis for extended oil change intervals. | API GL-4/GL-5 | – | VOLVO 97310 |
| Automatic Transmission Fluids (ATF) | | | | |
| TITAN ATF 6400 | Premium Performance ATF with reduced viscosity specifically formulated for automatic transmissions. Licensed according to DEXRON VI and MERCON LV. Product dyeing: red. | – | DEXRON VI FORD MERCON LV | AISIN WARNER/ AW-1 |
| TITAN ATF 4400 | Ultra High Performance ATF specifically formulated for passenger cars and light commercial vehicles. The high torque capacity exceeds the performance of many original fluids. Product dyeing: red. | – | – | DEXRON III FORD MERCON JWS 3309/TYP T-IV |

| Product name | Description | Specifications | Approvals | FUCHS Recommendations |
|--|--|--|-------------------------------|-------------------------------------|
| TITAN ATF 4000 | Ultra High Performance ATF for use in automatic transmissions as well as other ATF applications. Licensed according to DEXRON III (H). Improved low-temperature shifting compared to DEXRON II. Product dyeing: red. | – | DEXRON III (H) VOLVO 97341 | FORD MERCON |
| Central Hydraulic / Power Steering Fluids | | | | |
| TITAN CHF 11S | Premium Performance Power Steering and Central Hydraulic Fluid with a wide application and approval profile for various manufacturers. Product dyeing: green. | – | – | VOLVO 1161529 |
| TITAN CHF 202 | Premium Performance Power Steering and Central Hydraulic Fluid with a wide application and approval profile for various manufacturers. Product dyeing: green. | – | – | VOLVO 30741424 |
| Antifreeze | | | | |
| MAINTAIN FRICOFN LL | Premium Performance Coolant Additive based on monoethylene glycol. Free from nitrite, amine, phosphate and silicates. Product dyeing: orange. | ASTM D 3306 TYPE I | – | VOLVO COOLANT VCS (STD 418-0001) |
| MAINTAIN FRICOFN | Super High Performance Coolant Additive based on monoethylene glycol. Free from nitrite, amine and phosphate. Product dyeing: blue-green. | ASTM D 3306 TYPE I | – | – |
| Brake Fluids | | | | |
| MAINTAIN DOT 4 LV | Premium Performance Brake Fluid for hydraulic brake systems and clutch actuation in passenger cars, trucks and motorcycles. | FMVSS NR. 116 DOT 3/4 ISO 4925 CLASS 3/4/6 JIS K2233 CLASS 3/4/6 SAE J 1703/1704 | – | – |
| MAINTAIN DOT 5.1 | Ultra High Performance Brake Fluid for hydraulic brake systems and clutch actuation in passenger cars, trucks and motorcycles. | FMVSS NR. 116 DOT 3/4/5.1 ISO 4925 CLASS 3/4/5-1 JIS K2233 CLASS 3/4/5 SAE J1703/J1704 | – | – |

The information contained in this product information is based on the experience and know-how of FUCHS SCHMIERSTOFFE GMBH in the development and manufacturing of lubricants and represents the current state-of-the-art. The performance of our products can be influenced by a series of factors, especially the specific use, the method of application, the operational environment, component pre-treatment, possible external contamination, etc. For this reason, universally-valid statements about the function of our products are not possible. Our products must not be used in aircraft or spacecraft. Our products may be used in the manufacture of components for aircraft or spacecraft if they are removed without residue from the components prior to assembly into the aircraft or spacecraft. The information given in this product information represents general, non-binding guidelines. No warranty expressed or implied is given concerning the properties of the product or its suitability for any given application. We therefore recommend that you consult a FUCHS SCHMIERSTOFFE GMBH application engineer to discuss application conditions and the performance criteria of the products before the product is used. It is the responsibility of the user to test the functional suitability of the product and to use it with the corresponding care. Our products undergo continuous improvement. We therefore retain the right to change our product program, the products, and their manufacturing processes as well as all details of our product information sheets at any time and without warning, unless otherwise provided in customer-specific agreements. With the publication of this product information, all previous editions cease to be valid.
Any form of reproduction requires express prior written permission from FUCHS SCHMIERSTOFFE GMBH.
© FUCHS SCHMIERSTOFFE GMBH. All Rights reserved. Issue 03/2021

FUCHS SCHMIERSTOFFE GMBH
Export Division • Friesenheimer Straße 19 • 68169 Mannheim/Germany
Phone: +49 621 3701-1703 • Fax: +49 621 3701-7719
E-Mail: export-fs@fuchs.com • www.fuchs.com/de/en

PARTNER
des deutschen Kraftfahrzeuggewerbes

