



LUBRICANTS FOR RENAULT COMMERCIAL VEHICLES



Quality counts. As one of the leading factory fill specialists we supply high performance quality. Today and tomorrow. FUCHS offers also the right lubricants for Renault.

Product name	Description	Specifications	Approvals	FUCHS Recommendations
Engine Oils				
TITAN CARGO MAXX SAE 5W-30 	Premium MAXX Performance Engine Oil with new XTL®-Technology. Specially developed for vehicles with modern exhaust after treatment and turbocharger. Optimum cold starting properties and ageing stability for extreme fuel-economy over the whole drain-interval.	ACEA E9/E7/E6/E4 API CK-4/CJ-4 JASO DH-1/DH-2/DL-0	RENAULT RLD-3	–
TITAN CARGO MAXX SAE 10W-30	Premium MAXX Performance Engine Oil specially developed for vehicles with modern exhaust after treatment and turbocharger. Good cold starting properties and excellent ageing stability for fuel-economy over the whole drain-interval.	ACEA E9/E7/E6 API CK-4/SN	RENAULT RLD-3	JASO DH-2 RENAULT RLD-4
TITAN CARGO MAXX II SAE 10W-40 	Premium MAXX Performance Engine Oil with new XTL®-Technology. Specially developed for vehicles with modern exhaust after treatment and turbocharger. Good cold starting properties and ageing stability for fuel-economy over the whole drain-interval.	ACEA E9/E7/E6/E4 API CK-4/CJ-4 JASO DH-2	RENAULT RLD-3	–
TITAN CARGO SL SAE 5W-30	Ultra High Performance, extreme fuel-economy engine oil for a variety of commercial vehicle diesel engines, with optimum cold starting and lower oil consumption. Specially developed for extended service intervals.	ACEA E7/E4	RENAULT RXD/RLD-2	–
TITAN CARGO LA SAE 5W-30	Ultra High Performance, extreme fuel-economy engine oil, specially developed for commercial vehicles with modern exhaust after treatment systems and turbocharger. Offers good cold starting and lower oil consumption.	ACEA E9/E7/E6 API CI-4 JASO DH-2	RENAULT RLD-2/RXD/RGD	–
TITAN CARGO LA SAE 10W-40	Ultra High Performance, fuel-economy engine oil, specially developed for commercial vehicles with modern exhaust after treatment systems and turbocharger. Offers good cold starting and lower oil consumption.	ACEA E9/E7/E6 API CI-4 JASO DH-2	RENAULT RLD-2/RXD/RGD	–
TITAN CARGO PRO 228.61 SAE 5W-30	Ultra High Performance, extreme fuel-economy engine oil. Specially developed for Mercedes Benz commercial vehicles with modern exhaust after treatment systems. Suitable for Euro VI engines. Offers good cold starting and lower oil consumption.	API FA-4	–	RENAULT RLD-5
TITAN CARGO LD3 SAE 10W-40	Ultra High Performance, fuel-economy engine oil. Specially developed for extended service intervals.	ACEA E7/E4	RENAULT RLD-2	API CF
TITAN CARGO MC SAE 10W-40	Ultra High Performance, fuel-economy engine oil based on MC-synthesis for a variety of commercial vehicle diesel engines. Specially developed for extended service intervals. Good cold starting and lower oil consumption.	ACEA E7/E4 API CI-4 GLOBAL DHD-1	RENAULT RXD/RLD-2	–
TITAN CARGO SAE 5W-40	Ultra High Performance, fuel-economy engine oil, specially developed for commercial vehicle diesel engines with extended service intervals, exhaust after treatment and turbocharger.	ACEA E9 API CK-4/CJ-4/SN	RENAULT RLD-3	RENAULT RLD-3
TITAN CARGO SAE 10W-30	Ultra High Performance, fuel-economy engine oil, specially developed for commercial vehicle diesel engines with extended service intervals, exhaust after treatment and turbocharger.	ACEA E9 API CK-4/CJ-4 JASO DH-2	RENAULT RLD-3	–
TITAN CARGO SAE 10W-40	Ultra High Performance, fuel-economy engine oil, specially developed for commercial vehicle diesel engines with extended service intervals, exhaust after treatment and turbocharger.	ACEA E9/E7 API CK-4 JASO DH-2	RENAULT RLD-3	RENAULT RLD-4

LUBRICANTS FOR RENAULT COMMERCIAL VEHICLES



Product name	Description	Specifications	Approvals	FUCHS Recommendations
TITAN CARGO SAE 15W-40	Ultra High Performance, fuel-economy engine oil for a variety of commercial vehicle diesel engines. Specially developed for vehicles with extended service intervals, exhaust after treatment and turbocharger.	ACEA E9 API CK-4/CJ-4/SN JASO DH-2	RENAULT RLD-3	RENAULT RLD-4
TITAN CARGO CC SAE 10W-40	Ultra High Performance, fuel-economy engine oil based on MC-synthesis for a variety of commercial vehicle diesel engines. Specially developed for extended service intervals. Good cold starting and lower oil consumption. Further optimised for low temperature flow performance.	ACEA E4/E7	–	API CF RENAULT RXD/RLD/RD-2/RLD-2
TITAN TRUCK PLUS SAE 15W-40	Super High Performance Engine Oil for a variety of diesel and gasoline engines. Specially for highly-loaded commercial vehicle diesel engines. Lower oil consumption.	ACEA E7 API CI-4/SL GLOBAL DHD-1	RENAULT RLD/RLD-2	ALLISON C-4
Engine Oil for Commercial Vehicles with Gas Engines				
TITAN CARGO PRO GAS SAE 10W-40	Premium Performance, extreme fuel-economy engine oil for highly-supercharged commercial vehicle gas engines as well as Diesel engines with exhaust gas after treatment systems. Specially developed for gas powered engines with and without turbocharger. Optimum cold starting, lower oil consumption and minimized exhaust emissions.	ACEA E9/E7/E6	RENAULT RLD-2	–
Gear Oils				
TITAN CYTRAC TD SAE 75W-90	Premium Performance Gear Oil for highly-stressed manual transmissions and hypoid axles in commercial vehicles formulated with fully-synthetic base oils. Developed for the longest oil change intervals.	API GL-4/GL-5 API MT-1 SAE J2360	VOLVO 97312	–
TITAN CYTRAC SL SAE 75W-90	Premium Performance Gear Oil for highly-stressed hypoid axles in commercial vehicles formulated with fully-synthetic base oils. Developed for the longest oil change intervals in commercial vehicle axle drives.	API GL-5	–	VOLVO 97312
TITAN CYTRAC ULTRA SYNTH SAE 75W-80	Premium Performance Gear Oil for gear boxes in commercial vehicles, especially developed for ZF heavy duty transmissions with and without Intarder. Reduces fuel consumption by improving gearbox efficiency. Suitable for longest oil change intervals.	API GL-4 VOLVO 97307	–	–
TITAN CYTRAC MAT SAE 75W-80	Premium Performance Gear Oil for gear boxes in commercial vehicles, specially developed for manual and automatic ZF-gear boxes, formulated with selected base oils. Reduces fuel consumption by improving gearbox efficiency. Suitable for the longest oil change intervals and compatible with Carbon-Synchronizers.	API GL-4	VOLVO 97307	VOLVO 97305
TITAN SUPERGEAR MC SAE 80W-90	Super High Performance Gear Oil based on MC-Synthesis for extended oil change intervals.	API GL-4/GL-5	–	VOLVO 97310
TITAN SUPERGEAR MC SAE 80W-140	Super High Performance Gear Oil based on MC-Synthesis for extended oil change intervals.	API GL-4/GL-5	–	RENAULT VI
Automatikgetriebeöle (ATF)				
TITAN ATF 5500	Premium Performance ATF for automatic transmission in motor vehicles. Outstanding base oil quality for optimal cold temperature properties and high ageing stability. Durable friction properties for excellent wet clutch performance. Product dyeing: none.	–	VOLVO 97341	–

Product name	Description	Specifications	Approvals	FUCHS Recommendations
TITAN ATF 4000	Ultra High Performance ATF for use in automatic transmissions as well as other ATF applications. Licensed according to DEXRON III (H). Improved low-temperature shifting compared to DEXRON II. Product dyeing: red.	–	VOLVO 97341	–
Antifreeze				
MAINTAIN FRICOFIN LL	Premium Performance Coolant Additive based on monoethylene glycol. Free from nitrite, amine, phosphate and silicates. Product dyeing: orange.	ASTM D 3306 TYPE I ASTM D 6210 TYPE I-FF BS 6580:2010 SAE J814 FVV Heft R443 KSM 2142	Bez.Reg.Arnsbg. E62.12.22.64- 2011-1	AS/NZS 2108:2004 TYPE A ASTM D 4985 SAE J1034 JASO M325 JIS K2234 RENAULT 41-01- 001/- -S Type D
MAINTAIN FRICOFIN LL 50	Premium Performance Coolant Ready-Mix based on monoethylene glycol. Free from nitrite, amine, phosphate and silicates. Offers frost protection down to -35°C. Product dyeing: orange.	ASTM D 3306 TYPE III ASTM D 6210 TYPE III-FF BS 6580:2010	–	ASTM D 4985 SAE J1034 Bez.Reg.Arnsbg. E62.12.22.64-2011-1 RENAULT 41-01- 001/- -S Type D

The information contained in this product information is based on the experience and know-how of FUCHS SCHMIERSTOFFE GMBH in the development and manufacturing of lubricants and represents the current state-of-the-art. The performance of our products can be influenced by a series of factors, especially the specific use, the method of application, the operational environment, component pre-treatment, possible external contamination, etc. For this reason, universally-valid statements about the function of our products are not possible. Our products must not be used in aircraft or spacecraft. Our products may be used in the manufacture of components for aircraft or spacecraft if they are removed without residue from the components prior to assembly into the aircraft or spacecraft. The information given in this product information represents general, non-binding guidelines. No warranty expressed or implied is given concerning the properties of the product or its suitability for any given application. We therefore recommend that you consult a FUCHS SCHMIERSTOFFE GMBH application engineer to discuss application conditions and the performance criteria of the products before the product is used. It is the responsibility of the user to test the functional suitability of the product and to use it with the corresponding care. Our products undergo continuous improvement. We therefore retain the right to change our product program, the products, and their manufacturing processes as well as all details of our product information sheets at any time and without warning, unless otherwise provided in customer-specific agreements. With the publication of this product information, all previous editions cease to be valid.

Any form of reproduction requires express prior written permission from FUCHS SCHMIERSTOFFE GMBH.
© FUCHS SCHMIERSTOFFE GMBH. All Rights reserved. Issue 03/2021

FUCHS SCHMIERSTOFFE GMBH
Export Division • Friesenheimer Straße 19 • 68169 Mannheim/Germany
Phone: +49 621 3701-1703 • Fax: +49 621 3701-7719
E-Mail: export-fs@fuchs.com • www.fuchs.com/de/en

PARTNER
des deutschen Kraftfahrzeuggewerbes

