

FUCHS Special Applications

CEPLATTYN CLEANER – Cleaning of Open Gears



MOVING YOUR WORLD



CEPLATTYN CLEANER is a special cleaner with very good lubrication properties. CEPLATTYN CLEANER has been especially developed for a dynamic cleaning of Open Gear systems used in cement, mining and power generation industries.

Why clean an Open Gear?

A clean Open Gear facilitates any work on the drive:

- maintenance work like repair and grinding as well as periodical checks, e.g. crack inspection and static wear measurements
- reversal of a gear set
- replacement of a gear set

Product Features:

- excellent cleaning effect
- very good wear protection during dynamic cleaning
- corrosion protection properties
- highly effective application via commercially available high pressure cleaner
- also suitable for the cleaning of other metallic components, e.g. chains, wire ropes and articulated joints

CEPLATTYN CLEANER is a very cost-effective cleaning solution.

Service

In addition to our outstanding regular inspection service for Open Gears including vibration measurements, temperature measurements, checking the contact pattern of the tooth flanks etc., our customers benefit from our Open Gear cleaning service, being part of our extended service

Possible cost savings:

- consumption reduction of up to 50% while maintaining its cleaning effect, compared to conventional Open Gear cleaners
- saved time through fast cleaning procedure with reduced work effort
- reduced waste due to lower cleaner consumption and less operating supplies
- less manpower required
- reduced down time of machinery

For further information please refer to product-related documents such as product information and safety data sheet.



range, that also covers re-profiling, removal of pitting, alignment, etc.

CEPLATTYN CLEANER may only be applied onto Open Gears by specialists trained by FUCHS experts.

FUCHS LUBRICANTS GERMANY GmbH
Friesenheimer Str. 19
68169 Mannheim/Germany
Phone +49 621 3701-0
zentrale-flg@fuchs.com
www.fuchs.com/de

The information contained in this product information is based on the experience and expertise of FUCHS LUBRICANTS GERMANY GmbH in the development and manufacturing of lubricants, and represents the current cutting edge. The performance of our products can be influenced by a series of factors, especially the specific use, the method of application, the operational environment, component pretreatment, possible external contamination, etc. For this reason, universally valid statements about the function of our products are not possible. Our products must not be used in aircraft/spacecraft or their components, unless such products are removed before the components are assembled into the aircraft/spacecraft. The information given in this product information represents general, non-binding guidelines. No warranty expressed or implied is given concerning the properties of the product or its suitability for any given application. We therefore recommend that you consult a FUCHS LUBRICANTS GERMANY GmbH application engineer to discuss application conditions and the performance criteria of the products before the product is used. It is the responsibility of the user to test the functional suitability of the product and to use it with the corresponding care. Our products undergo continuous improvement. We therefore retain the right to change our product range, the products and their manufacturing processes as well as all details of our product information sheets at any time and without warning, unless otherwise provided in customer-specific agreements. With the publication of this product information, all previous editions cease to be valid. Any form of reproduction requires express prior written permission from FUCHS LUBRICANTS GERMANY GmbH.