



# DAIMLER TRUCK

LUBRICANTS FOR COMMERCIAL VEHICLES



Quality counts. As one of the leading factory fill specialists we supply high performance quality. Today and tomorrow. FUCHS offers also the right lubricants for Daimler Truck.

Product name	Description	Specifications	Approvals	FUCHS Recommendations
<b>Engine Oils</b>				
<b>TITAN CARGO MAXX II SAE 5W-30</b> 	Premium MAXX Performance Engine Oil with new XTL-Technology. Specially developed for vehicles with modern exhaust after treatment and turbocharger. Optimum cold starting properties and ageing stability for extreme fuel-economy over the whole drain-interval.	ACEA E11, E9, E8, E7, E6, E4 API CK-4/CJ-4	MB- APPROVAL 228.31 MB- APPROVAL 228.51 MB- APPROVAL 228.52	–
<b>TITAN CARGO MAXX II SAE 10W-40</b> 	Premium MAXX Performance Engine Oil with new XTL-Technology. Specially developed for vehicles with modern exhaust after treatment and turbocharger. Good cold starting properties and ageing stability for fuel-economy over the whole drain-interval.	ACEA E11, E9, E8, E7, E6, E4 API CK-4/CJ-4	MB- APPROVAL 228.31 MB- APPROVAL 228.51 MB- APPROVAL 228.52	–
<b>TITAN CARGO SL SAE 5W-30</b>	Premium Performance, extreme fuel-economy engine oil for a variety of commercial vehicle diesel engines, with optimum cold starting and lower oil consumption. Specially developed for extended service intervals.	ACEA E7, E4	MB- APPROVAL 228.5 MB- APPROVAL 235.28	–
<b>TITAN CARGO PRO 228.61 SAE 5W-30</b>	Premium Performance, extreme fuel-economy engine oil. Specially developed for Mercedes Benz commercial vehicles with modern exhaust after treatment systems. Suitable for Euro VI engines. Offers good cold starting and lower oil consumption.	API FA-4	MB- APPROVAL 228.61	–
<b>TITAN CARGO MC SAE 10W-40</b>	Premium Performance, fuel-economy engine oil based on MC-synthesis for a variety of commercial vehicle diesel engines. Specially developed for extended service intervals. Good cold starting and lower oil consumption.	ACEA E7, E4 API CI-4	MB- APPROVAL 228.5	–
<b>Gear Oils</b>				
<b>TITAN CYTRAC TD SAE 75W-90</b>	Premium Performance Gear Oil for highly-stressed manual transmissions and hypoid axles in commercial vehicles formulated with fully-synthetic base oils. Developed for the longest oil change intervals.	API GL-4/GL-5 API MT-1 SAE J2360	MB- APPROVAL 235.8	–
<b>TITAN CYTRAC PRO 235.31 SAE 75W-85</b>	Premium Performance Gear Oil for highly-stressed hypoid axles in Mercedes-Benz commercial vehicles formulated with selected base oils. Developed for the longest oil change intervals and optimized gearbox efficiency.	API GL-5	MB- APPROVAL 235.31	–
<b>TITAN CYTRAC FE SYNTH SAE 75W-85</b>	Premium Performance Gear Oil for gear boxes in commercial vehicles, specially for the latest version of Mercedes-Benz CO <sub>2</sub> transmissions, formulated with fully-synthetic base oils. Most fuel efficient by improving gearbox efficiency. Suitable for the longest oil change intervals.	API GL-4	MB- APPROVAL 235.16	–
<b>TITAN CYTRAC MB SYNTH SAE 75W-90</b>	Premium Performance Gear Oil for gear boxes in commercial vehicles, specially developed for Mercedes-Benz Actros vehicles, formulated with fully-synthetic base oils. Reduces fuel consumption by improving gearbox efficiency. Suitable for the longest oil change intervals.	API GL-4	MB- APPROVAL 235.11	–
<b>TITAN CYTRAC ULTRA SYNTH SAE 75W-80</b>	Premium Performance Gear Oil for gear boxes in commercial vehicles, especially developed for ZF heavy duty transmissions with and without Intarder. Reduces fuel consumption by improving gearbox efficiency. Suitable for longest oil change intervals.	API GL-4	–	MB 235.29 MB 235.41
<b>TITAN GEAR HYP LD SAE 80W-90</b>	High Performance Gear Oil specially developed for Mercedes-Benz commercial vehicles. Offering enhanced thermal stability and fuel-economy potential.	API GL-5 API MT-1 SAE J2360	MB- APPROVAL 235.20	–


# DAIMLER TRUCK

LUBRICANTS FOR COMMERCIAL VEHICLES

Product name	Description	Specifications	Approvals	FUCHS Recommendations
<b>TITAN SUPERGEAR MC SAE 80W-90</b>	Ultra High Performance Gear Oil based on MC-Synthesis for extended oil change intervals.	API GL-4/GL-5	MB- APPROVAL 235.0	–
<b>TITAN GEAR MP SAE 80</b>	High Performance Gear Oil for synchronized and non-synchronized manual gearboxes as well as auxiliary drives, axles and differentials in commercial vehicles and passenger cars.	API GL-4	MB- APPROVAL 235.1	–
<b>Automatic Transmission Fluids (ATF)</b>				
<b>TITAN ATF 5500</b>	Premium Performance ATF for automatic transmission in motor vehicles. Outstanding base oil quality for optimal cold temperature properties and high ageing stability. Durable friction properties for excellent wet clutch performance. Product dyeing: none.	–	MB- APPROVAL 236.9	–
<b>TITAN ATF 4000</b>	Ultra High Performance ATF for use in automatic transmissions as well as other ATF applications. Licensed according to DEXRON III (H). Improved low-temperature shifting compared to DEXRON II. Product dyeing: red.	–	MB- APPROVAL 236.1 MB- APPROVAL 236.9	–
<b>Central Hydraulic / Power Steering Fluids</b>				
<b>TITAN CHF 11S</b>	Premium Performance Power Steering and Central Hydraulic Fluid with a wide application and approval profile for various manufacturers. Product dyeing: green.	–	MB- APPROVAL 345.0	–
<b>TITAN PSF</b>	High Performance Power Steering Fluid approved by Mercedes-Benz for passenger cars and commercial vehicles. Product dyeing: none.	–	MB- APPROVAL 236.3	–
<b>Antifreeze</b>				
<b>MAINTAIN FRICOFIN LL</b>	Premium Performance Coolant Concentrate based on monoethylene glycol. Free of nitrites, amines, phosphates and silicates with OAT-technology. Product dyeing: orange.	ASTM D 3306 TYPE I ASTM D 6210 TYPE I-FF	MB- APPROVAL 325.3	–
<b>MAINTAIN FRICOFIN DP</b>	Premium Performance Coolant Concentrate based on monoethylene glycol. Free of nitrites, amines and phosphates with Si-OAT-technology. Product dyeing: pink-violet.	ASTM D 3306 TYPE I ASTM D 4985	MB- APPROVAL 325.5 MB- APPROVAL 325.6	–

# DAIMLER TRUCK

LUBRICANTS FOR COMMERCIAL VEHICLES

Product name	Description	Specifications	Approvals	FUCHS Recommendations
<b>Brake Fluids</b>				
<b>MAINTAIN DOT 514 LV</b>  		FMVSS NR. 116 DOT 3/4/5.1 ISO 4925 CLASS 3/4/5- 1/6/7 JIS K2233 CLASS 3/4/5/6 SAE J 1703/1704	–	MB 331.0

The information contained in this product information is based on the experience and know-how of FUCHS LUBRICANTS GERMANY GmbH in the development and manufacturing of lubricants and represents the current state-of-the-art. The performance of our products can be influenced by a series of factors, especially the specific use, the method of application, the operational environment, component pre-treatment, possible external contamination, etc. For this reason, universally-valid statements about the function of our products are not possible. Our products must not be used in aircraft or spacecraft. Our products may be used in the manufacture of components for aircraft or spacecraft if they are removed without residue from the components prior to assembly into the aircraft or spacecraft. The information given in this product information represents general, non-binding guidelines. No warranty expressed or implied is given concerning the properties of the product or its suitability for any given application. We therefore recommend that you consult a FUCHS LUBRICANTS GERMANY GmbH application engineer to discuss application conditions and the performance criteria of the products before the product is used. It is the responsibility of the user to test the functional suitability of the product and to use it with the corresponding care. Our products undergo continuous improvement. We therefore retain the right to change our product program, the products, and their manufacturing processes as well as all details of our product information sheets at any time and without warning, unless otherwise provided in customer-specific agreements. With the publication of this product information, all previous editions cease to be valid. Any form of reproduction requires express prior written permission from FUCHS LUBRICANTS GERMANY GmbH. © FUCHS LUBRICANTS GERMANY GmbH. All Rights reserved. Issue 12/2022

FUCHS LUBRICANTS GERMANY GmbH  
Export Division • Friesenheimer Straße 19 • 68169 Mannheim/Germany  
Phone: +49 621 3701-1703 • Fax: +49 621 3701-7719  
E-Mail: export-flg@fuchs.com • www.fuchs.com/de/en

**PARTNER**  
des deutschen Kraftfahrzeuggewerbes

