

Pharmaceutical White Oils & Process Oils

MOVING YOUR WORLD



Pharmaceutical White Oils

Product name	Colour Saybolt ASTM D156	Kin. viscosity at 40 °C [mm ² /s] ASTM D7042	Density at 15 °C [g/cm ³] ASTM D4052	Flash point [°C] ASTM D92, COC
Pharma White Oil PL 501A	min. +30	ca. 16	ca. 0.850	ca. 195
Pharma White Oil PL 501B	min. +30	ca. 24	ca. 0.855	ca. 204
Pharma White Oil PL 1301*	min. +30	ca. 35	ca. 0.862	ca. 218
Pharma White Oil PL 500A*	min. +30	ca. 47	ca. 0.864	ca. 225
Pharma White Oil PL 500	min. +30	ca. 71	ca. 0.867	ca. 254
Pharma White Oil PL 420*	min. +30	ca. 100	ca. 0.870	ca. 256

* All of our Pharma White Oils meet the requirements of the Ph.Eur. The viscosity of Pharma White Oil PL 1301, PL 500A and PL 420 may be outside of Ph. Eur. requirement.
We can also supply you with NSF-listed products from our pharmaceutical white oil range. Please contact us.

Process Oils

Product name	Colour	Kin. viscosity at 40 °C [mm ² /s] ASTM D445	Density at 15 °C [g/cm ³] ASTM D4052	Flash point [°C]
PUROFLUID 445	ca. +30 ASTM D156	ca. 16	ca. 0.855	ca. 190 ASTM D92, COC
PUROFLUID 430	ca. +24 ASTM D156	ca. 17	ca. 0.861	ca. 203 ASTM D92, COC
PUROFLUID 2060	ca. +0.5 ASTM D1500	ca. 32	ca. 0.841	ca. 240 ASTM D92, COC
PUROFLUID 74	< 3.0 ASTM D1500	ca. 490	ca. 0.900	ca. 300 ASTM D92, COC
PUROFLUID 367*	ca. +10 ASTM D156	ca. 87	ca. 0.898	ca. 220 ASTM D93, PMCC

* Naphthenic oil

The information contained in this product information is based on the experience and know-how of FUCHS LUBRICANTS GERMANY GmbH in the development and manufacturing of lubricants and represents the current state-of-the-art. The performance of our products can be influenced by a series of factors, especially the specific use, the method of application, the operational environment, component pre-treatment, possible external contamination, etc. For this reason, universally-valid statements about the function of our products are not possible. Our products must not be used in aircraft or spacecraft. Our products may be used in the manufacture of components for aircraft or spacecraft if they are removed without residue from the components prior to assembly into the aircraft or spacecraft. The information given in this product information represents general, non-binding guidelines. No warranty expressed or implied is given concerning the properties of the product or its suitability for any given application. We therefore recommend that you consult a FUCHS LUBRICANTS GERMANY GmbH application engineer to discuss application conditions and the performance criteria of the products before the product is used. It is the responsibility of the user to test the functional suitability of the product and to use it with the corresponding care. Our products undergo continuous improvement. We therefore retain the right to change our product program, the products, and their manufacturing processes as well as all details of our product information sheets at any time and without warning, unless otherwise provided in customer-specific agreements. With the publication of this product information, all previous editions cease to be valid. Any form of reproduction requires express prior written permission from FUCHS LUBRICANTS GERMANY GmbH.

© FUCHS LUBRICANTS GERMANY GmbH. All Rights reserved. Issue 01 / 2024

FUCHS LUBRICANTS GERMANY GmbH

Industriestraße 35-53 ▪ 22880 Wedel/Germany ▪ Phone: 04103 9134-19 ▪ E-mail: info-paraf fluid@fuchs.com ▪ www.fuchs.com/de/en