

FUCHS AUTOGREASER

PRODUCT OVERVIEW

Automatic Lubricator



- Puts you in complete control of your lubrication programme. The FUCHS AUTOGREASER provides a constant, controlled flow of grease, exactly where it's needed, without interrupting production.
- Is completely self contained. No tools or components are needed and it is available pre-loaded with either FUCHS RENOLIT LX EP2 or RENOLIT CSX15 grease.
- Is easy to install. It simply screws into a standard grease nipple socket, or into any other lubrication point, to enable awkwardly placed bearings to be lubricated without the need to stop machinery.
- Works in any position. The FUCHS AUTOGREASER can be fitted in any conveniently accessible position on its side, upside down, on moving parts or even in water.
- Is easy to operate. With 7 variable discharge periods, ranging from 1 - 12 months, it will supply continuous lubrication, without attention, until the allotted life-span is over. Discharge levels are visibly displayed and a pressure relief valves warns of blocked greaseways.
- Can reduce the cost of scheduled preventative maintenance. The FUCHS AUTOGREASER is a reliable way to extend component and equipment life while reducing down time and is suitable for most industrial applications.
- Is suitable for all industries. Can be used in quarrying, water, mining, steel, paper and other process industries.

LUBRICANTS.
TECHNOLOGY.
PEOPLE.



Never under-estimate the importance of the right lubricating grease! Greases are an integral part of achieving optimum performance. FUCHS RENOLIT greases cover a wide variety of applications and specifications to ensure that things run smoothly. The FUCHS AUTOGREASER comes pre-loaded with one of two carefully selected greases.

RENOLIT CSX 15

RENOLIT CSX 15 is a calcium sulphonate complex grease that has been specially developed using only the finest base oils. With advanced anti-wear and extreme pressure additives, it has excellent water resistance, corrosion protection and oil separation characteristics and is particularly suited to working under the severe conditions in plain and roller bearings. RENOLIT CSX 15 is easily pumpable even in long tubes, fed by centralised lubrication systems.

RENOLIT LX EP 2

RENOLIT LX EP 2 is a multi-purpose, grease designed to give long-life even at ambient and high temperatures. It is lead free and contains extreme pressure, anti-oxidant and anti-corrosion additives. RENOLIT LX EP 2 provides good rust protection, efficient water resistance and excellent stability against oxidation. These properties enable it to resist mechanical breakdown while lubricating front wheel bearings efficiently, despite transmitted heat.

PRODUCT	COLOUR	NLGI GRADE	THICKENER	SPECS.	APPLICATION	TYPICAL INDUSTRIES
RENOLIT CSX 15	Light brown	2/1	Calcium sulphonate complex	-	Heavily loaded rolling or plain bearings	Steel and paper mills, mining, concrete, quarry and construction equipment
RENOLIT LX EP 2	Amber	2	Lithium complex	Ford Motor Co. Specification WSD-M1C-228A and SAM 1C 9111A. Leyland Bus Specification GX	Multi-purpose long-life grease for high hold and high temperature operations	Suitable for the majority of industrial and automotive applications

Product and safety data sheets for all grades are available upon request

FUCHS LUBRICANTS (UK) PLC

New Century Street,
Hanley, Stoke-on-Trent,
ST1 5HU
Phone: +44 (0)1782 203 700
Email: contact-uk@fuchs-oil.com
www.fuchslubricants.com