

LUBRICANTS FOR MAZDA PASSENGER CARS



Quality counts. As one of the leading factory fill specialists we supply high performance quality. Today and tomorrow. Therefore Mazda counts on lubricants and specialities of FUCHS.

| Product | Description | Specifications | Approvals | FUCHS Recommendations |
|---|--|------------------------------------|-----------|-----------------------|
| Engine Oils | | | | |
| TTAN GT1 PRO C-3 SAE 5W-30 | Premium Performance, extreme fuel-economy engine oil with new XTL®-Technology for optimum cold start ability and outstanding performance reserves. For modern passenger cars and light commercial vehicles with or without extended service intervals. Specially developed for vehicles with exhaust after treatment and turbocharger. | ACEA C3 API SN | – | – |
| TTAN GT1 PRO C-1 SAE 5W-30 | Premium Performance, extreme fuel-economy engine oil for modern passenger cars and light commercial vehicles with or without extended service intervals. Specially developed for vehicles with exhaust after treatment and turbocharger. Optimum cold starting, lower oil consumption and minimized exhaust emissions. | ACEA C1 | – | JASO DL-1 |
| TTAN Supersyn F Eco -DT SAE 5W-30 | Ultra High Performance, extreme fuel-economy engine oil. Optimum cold starting and lower oil consumption. | ACEA A1/B1 ACEA A5/B5 API SL | – | API CF |
| TTAN Supersyn SAE 5W-30 | Ultra High Performance, extreme fuel-economy engine oil for a variety of vehicles with or without extended service intervals. Optimum cold starting and lower oil consumption. | ACEA A3/B4 API SL | – | API CF |
| TTAN SYN MC SAE 10W-40 | Super High Performance, fuel-economy engine oil based on MC-synthesis for a variety of gasoline and diesel engines in passenger cars. Lower oil consumption. | ACEA A3/B4 API SN | – | API CF |
| Gear Oils | | | | |
| TTAN SINTOFLUID SAE 75W-80 | Premium Performance Manual Transmission Fluid for passenger cars. Offering good gearbox efficiency. Suitable as fill for life fluid according to manufacturer. | API GL-5 | – | – |
| TTAN SINTOPOID SAE 75W-90 | Premium Performance Axle Gear Oil for passenger cars, also for high-offset hypoid drives offering good gearbox efficiency. Suitable as fill for life fluid according to manufacturer. | API GL-5 | – | – |
| TTAN SUPERGEAR MC SAE 80W-90 | Super High Performance Gear Oil based on MC-Synthesis for extended oil change intervals. | API GL-4/GL-5 | – | – |

| Product | Description | Specifications | Approvals | FUCHS Recommendations |
|--|--|--|-----------|--|
| Automatic Transmission Fluids (ATF) | | | | |
| TTAN ATF 4400 | Ultra High Performance ATF specifically formulated for Japanese passenger cars and light commercial vehicles, as well as for several European and American manufacturers. The high torque capacity exceeds the performance of many original fluids. Product dyeing: red. | – | – | DEXRON III FORD MERCON JWS 3309/TYPE T-IV MAZDA ATF D-III/ATF M-3 |
| TTAN ATF CVT | Ultra High Performance ATF specially designed for use in many CVT-gearboxes using push-belts or transmission chains made of steel. Product dyeing: none. | – | – | FORD MERCON C MAZDA CVTF 3320 |
| TTAN ATF 3353 | Ultra High Performance DEXRON III-generation-ATF for automatic transmissions as well as any other ATF-applications. Developed for automatic transmissions and transfer cases according manufacturer. Offers fuel-efficiency potential. Product dyeing: red. | – | – | DEXRON III FORD M2C202-B |
| TTAN ATF 3000 | Super High Performance DEXRON II (D) ATF for automatic transmissions in commercial vehicles, machinery and passenger cars according to manufacturer's documentation. Product dyeing: red. | – | – | DEXRON II (D) FORD MERCON FORD ESP-M2C166-H |
| Antifreeze | | | | |
| MAINTAIN FRICOFIN LL | Premium Performance Coolant Additive based on monoethylene glycol. Free from nitrite, amine, phosphate and silicates. Product dyeing: orange. | ASTM D 3306 TYPE I ASTM D 6210 TYPE I-FF BS 6580:2010 SAE J814 | – | ASTM D 4985 SAE J1034 MAZDA MEZ MN 121 D |
| MAINTAIN FRICOFIN | Super High Performance Coolant Additive based on monoethylene glycol. Free from nitrite, amine and phosphate. Product dyeing: blue-green. | ASTM D 3306 TYPE I ASTM D 4985 SAE J814 SAE J1034 BS 6580:2010 | – | – |
| Brake Fluids | | | | |
| MAINTAIN MAINTAIN DOT 5.1 | Ultra High Performance Brake Fluid for hydraulic brake systems and clutch actuation in passenger cars, trucks and motorcycles. | FMVSS NR. 116 DOT 5.1 ISO 4925 CLASS 3/4/5.1 SAE J 1703/J 1704 | – | – |

The information contained in this product information is based on the experience and know-how of FUCHS SCHMIERSTOFFE GMBH in the development and manufacturing of lubricants and represents the current state-of-the-art. The performance of our products can be influenced by a series of factors, especially the specific use, the method of application, the operational environment, component pre-treatment, possible external contamination, etc. For this reason, universally-valid statements about the function of our products are not possible. Our products must not be used in aircrafts/spacecrafts or their components, unless such products are removed before the components are assembled into the aircraft/spacecraft. The information given in this product information represents general, non-binding guidelines. No warranty expressed or implied is given concerning the properties of the product or its suitability for any given application. We therefore recommend that you consult a FUCHS SCHMIERSTOFFE GMBH application engineer to discuss application conditions and the performance criteria of the products before the product is used. It is the responsibility of the user to test the functional suitability of the product and to use it with the corresponding care. Our products undergo continuous improvement. We therefore retain the right to change our product program, the products, and their manufacturing processes as well as all details of our product information sheets at any time and without warning, unless otherwise provided in customer-specific agreements. With the publication of this product information, all previous editions cease to be valid. Any form of reproduction requires express prior written permission from FUCHS SCHMIERSTOFFE GMBH.
© FUCHS SCHMIERSTOFFE GMBH. All rights reserved. Edition 01/2018

FUCHS SCHMIERSTOFFE GMBH

Export Division ▪ Friesenheimer Straße 19 ▪ 68169 Mannheim/Germany

Phone: 0621 3701-1703 ▪ Fax: 0621 3701-7719

E-Mail: export@fuchs-schmierstoffe.de ▪ www.fuchs.com/de/en