

Gear oils for all vehicle types

MOVING YOUR WORLD



TITAN gear oils are the result of the latest research and development by the world's largest independent lubricant specialist together with leading automobile manufacturers, tailored to satisfy the demands of today's high-tech engines, offering outstanding high-performance, fuel-economy and wear protection.

Our gold, silver and bronze labelling helps identify your required quality quickly plus our latest packaging has been designed to make using our products easy and efficient. Ask your local FUCHS representative for more information.

Product	Specifications	Approvals	Recommendations
GEAR OILS FOR PASSENGER CARS			
TITAN SINTOFLUID FE SAE 75W	API GL-4	MB-APPROVAL 235.17	FORD WSS-M2C200-D2, MB 235.73, VW G 055 512 / VW TL 521 71 (G 052 171 A1 / A2) / VW TL 521 78 (G 052 178 A2) / VW TL 525 12 (G 052 512 A2) / VW TL 525 27 (G 052 527 A2) / VW TL 726 (G 052 726 A2 / G 055 726 A2 / G 060 726 A2 / G 070 726 A2)
TITAN SINTOFLUID SAE 75W-80	API GL-4	-	BMW 83 22 0 309 031 / BMW 83 22 0 403 247 / BMW 83 22 2 339 219 / BMW 83 22 7 533 818 / BMW 2300 1434 404 / BMW 2300 7533 513 / 818, FORD WSS-M2C200 C3, OPEL 19 40 182 / 19 40 757 / 19 40 768 / 19 40 776, VOLVO 97308, VW 501 50 (G 005 000 05 / G 005 000 / G 005 000 20 / G 052 911 A1/A2)
TITAN SINTOPOID FE SAE 75W-85	API GL-5	MB-APPROVAL 235.7 / 235.74 / 239.72, ZF TE-ML 18 (ZF002195)	MB 239.71, VW TL 521 45-X (G 052 145 A1) / VW TL 521 90 (G 052 190 A2/ G 055 190 A2)
TITAN SINTOPOID 4218 SAE 70W-80	API GL-5	BMW G3 (BMW 83 22 2 413 512) / BMW 83 22 2 460 180 / BMW 83 22 2 471 423	-
TITAN SINTOPOID SAE 75W-90	API GL-5	-	MIL-L-2105 D, VW TL 521 45-Y (G 052 145 A2)
TITAN SINTOPOID LS SAE 75W-90	API GL-4 / -5 / -5 incl. LS	-	FORD WSS-M2C200-C/C2, VW G50/G51
TITAN SINTOPOID LS SAE 75W-140	API GL-5	-	BMW 83 22 2 282 583 / BMW 83 22 9 407 870, CHRYSLER MS-8985, FORD WSL-M2C192-A, GM 12346140, JOHN DEERE JDM J11G, SCANIA STO 1:0
GEAR OILS FOR MIXED FLEETS			
TITAN SUPERGEAR MC SAE 80W-90	API GL-4 / GL-5	DTFR 12B100 (MB 235.0), EVOBUS 26.000-032 / 26.000-034, MAN 341 TYPE Z2 / 342 TYPE M2, MB-APPROVAL 235.0, SCANIA STO 1:0 / 1:1 G, ZF TE-ML 02B / 05A / 12L / 12M / 16B / 17H / 19B / 21A (ZF000722)	API MT-1, CASE MS 1316, FORD WSP-M2C197-A, JOHN DEERE JDM J11E, MAN M 3343 TYPE M / 341 TYPE E2, NH 520A, SDFG OP 1705, STEYR B-101, VOLVO 97310, ZF TE-ML 07 / 08
TITAN SUPERGEAR MC SAE 80W-140	-	SCANIA STO 1:0, ZF TE-ML 05A / 12M / 16C / 21A (ZF006028)	API MT-1 / API GL-4 / GL-5, JOHN DEERE JDM J11E, OPEL 19 42 386, RENAULT VI, VOLVO 97310, ZF TE-ML 08
TITAN SUPERGEAR PLUS SAE 80W-90	API GL-4 / GL-5, SAE J2360	MAN 342 TYPE M2, MB-APPROVAL 235.6, VOLVO 97321, ZF TE-ML 05A / 07A / 08 / 12E / 16B / 16C / 17B / 19B / 21A (ZFXXXXXX)	MB 235.0, MIL-L-2105 D/E, VOLVO 97310, NH 520A, STEYR B-101
TITAN SUPERGEAR SAE 80W-90	API GL-4 / GL-5	EVOBUS 26.000-025, MAN 342 TYPE M2, ZF TE-ML 05A / 12E / 17B / 19B / 21A (ZF000647)	MIL-L-2105 D, VOLVO 97310, NH 520A, STEYR B-101
TITAN SUPERGEAR SAE 85W-140	API GL-4 / GL-5	EVOBUS 26.000-025, ZF TE-ML 05A / 12E / 16D / 21A (ZF000650)	MIL-L-2105 D, VOLVO 97310
TITAN SUPERGEAR LS SAE 80W-90	API GL-5, SAE J306: 80W-90	ZF TE-ML 05N / 21N (ZFXXXXXX)	MIL-L-2105 D, FORD M2C104-A, JOHN DEERE JDM J11F, NH 520B, VOLVO 97310
TITAN GEAR LS SAE 90	API GL-5, SAE J306: 85W-90	ZF TE-ML 05C / 16E / 21C (ZF000651)	MIL-L-2105 D, FORD M2C104-A, JOHN DEERE JDM J11F, NH 520B, VOLVO 97310, ZF TE-ML 12C
TITAN GEAR MP SAE 80	API GL-4	MB-APPROVAL 235.1, ZF TE-ML 17A (ZF000654)	BMW MTF 1 (BMW 81 22 2 339 384) / BMW 81 22 9 407 052 / 053, FORD M2C9008-A, VW TL 726, ZF TE-ML 08
TITAN GEAR MP SAE 90	API GL-4	-	MAN 341 TYPE E1 / Z1, MB 235.1, ZF TE-ML 02A / 16A / 17A / 19A

Gear oils for all vehicle types

MOVING YOUR WORLD



Product	Specifications	Approvals	Recommendations
TITAN GEAR MP 80W-90	API GL-4	-	-
TITAN GEAR HYP SAE 90	API GL-5, SAE J306: 85W-90	DTFR 12B100 (MB 235.0) MB-APPROVAL 235.0, ZF TE-ML 16C, 17B, 19B, 21A (ZF000656)	FORD SR-M2C9102-A, JOHN DEERE JDM J11E, MAN 342 TYPE M1, OPEL 19 42 387, VOLVO 97310, VW TL 727, ZF TE-ML 07, 08
TITAN GEAR HYP 85W-140	API GL-5		MIL_L2105D, ZF TE-ML 07A
GEAR OILS FOR HEAVY DUTY VEHICLES			
TITAN CYTRAC TD SAE 75W-90	API GL-4/GL-5, API MT-1, SAE J2360	DETROIT DIESEL 93K219.01, MAN 341 TYPE Z2 / 342 TYPE S1, MB-APPROVAL 235.8, MERITOR O-76-E, SCANIA STO 1:0 / 1:1 G / 2:0 A FS, VOLVO 97312, ZF TE-ML 02B, 05A, 12L, 12N, 16F, 17B, 19C, 21A (ZF003341)*	JOHN DEERE JDM J11E / J11G, MAN 341 TYPE E3 / 342 TYPE M3
TITAN CYTRAC SL SAE 75W-90	API GL-5	MAN 342 TYPE S1, SCANIA STO 1:0	JOHN DEERE JDM J11E / J11G, MB 235.8, VOLVO 97312 ZF TE-ML 05B, 07, 08, 12B, 16F, 17B
TITAN CYTRAC PRO 235.31 SAE 75W-85	API GL-5	MB-APPROVAL 235.31	DETROIT DIESEL 93K219.03
TITAN CYTRAC PRO GA2 SAE 75W-90	API GL-5, SCANIA STO 1:1 G	MAN 341 TYPE GA2, SCANIA STO 2:0 G	-
TITAN CYTRAC PRO S2A SAE 75W-140	API GL-5, SCANIA STO 1:0	SCANIA STO 2:0 A	-
TITAN CYTRAC RR SAE 75W-90	API GL-5, API MT-1 SAE J2360	EvoBus 26.000-032 / 26.000-037, SCANIA STO 1:0, SIEMENS FLENDER Gear Units for Railway Vehicles, VOITH 132.00374401 / 132.00374402 / 3.325-340 / VOITH 3.325-342, ZF TE-ML 05A, 12L, 12N, 16F, 17B, 19C, 21A (ZF000732)	Gmeinder Getriebebau railway applications, ZF TE-ML 05B, 21B
TITAN CYTRAC ETN SAE 40	API MT-1	MERITOR O-81, CONMET, EATON PS-386 MACK TO-A PLUS, NAVISTAR MPAPS B-6816 TYPE II	EATON PS-164 REV 7
TITAN CYTRAC ETN-EP SAE 80W-140	API MT-1, API GL-5	DANA SHAE 429	ARVIN MERITOR O-80, O-76-B, INTERNATIONAL TMS 6816, MACK GO-J, SAE J2360, MIL-PRF-2105 E
TITAN CYTRAC FE SYNTH SAE 75W-85	API GL-4	MB-APPROVAL 235.16	-
TITAN CYTRAC MB SYNTH SAE 75W-90	API GL-4	MAN 341 TYPE MB, MB-APPROVAL 235.11	ZF TE-ML 08
TITAN CYTRAC ULTRA SYNTH SAE 75W-80	API GL-4, VOLVO 97307	EvoBus 26.000-030, MAN 341 TYPE Z5, ZF TE-ML 01L, 02L, 16K (ZF008388)	IVECO 18-1807 MSG2, MAN 341 TYPE VR, MB 235.29, MB 235.41, VOITH-RETARDER „C“
TITAN CYTRAC MAT SAE 75W-80	API GL-4	MAN 341 TYPE Z4, ZF TE-ML 01L, 02L, 16K (ZF003373)	IVECO 18-1807 CLASSE MGS1, MAN 341 TYPE E3 / TYPE Z3, TYPE Z5, VOLVO 97305 / 97307, ZF TE-ML 01E, 02D, 02E, 08, 16P
TITAN CYTRAC HSY SAE 75W-90	API GL-4/GL-5	EvoBus 26.000-032 / 26.000-037, ZF TE-ML 05A, 12L, 12N, 16F, 17B, 19C, 21A (ZF000642)	MAN 341 TYPE E3 / TYPE Z2 / 342 TYPE M3 / MAN M 3343 TYPE S, JOHN DEERE JDM J11E / J11G, SCANIA STO 1:0, ZF TE-ML 05B, 07, 21B
TITAN GEAR HYP LD SAE 80W-90	API GL-5, API MT-1, SAE J2360	DETROIT DIESEL 93K219.02, EvoBus 26.000-032 / 26.000-034, JOHN DEERE JDM J11E, MAN 342 TYPE M3, MB-APPROVAL 235.20, SCANIA STO 1:0, VOLVO 97321, ZF TE-ML 05A, 12L, 12M, 16B, 17B, 19B, 21A (ZF000645)	MIL-PRF-2105 E, ARVIN MERITOR O-76-D, MACK GO-J, ZF TE-ML 07A

FUCHS LUBRICANTS (UK) plc
New Century Street, Hanley,
Stoke on Trent, ST1 5HU
Telephone: +44 (0)1782 203700
E-Mail: contact-uk@fuchs.com
www.fuchs.com/uk

All information correct at time of publication.
Any form of reproduction requires express prior written permission from
FUCHS LUBRICANTS. © FUCHS LUBRICANTS. All rights reserved.