

High-tech lubricants for cars, bikes and commercial vehicles

2/2015



LUBRICANTS.
TECHNOLOGY.
PEOPLE.



LUBRICANTS. TECHNOLOGY. PEOPLE.



- _ World's largest independent lubricant specialist.**
- _ Complete ranges of industrial and automotive lubricants.**
- _ Leading first-fill competence for the German automotive industries.**
- _ Plants, Mannheim and Kiel.**



Numbers and facts

PLANT: MANNHEIM AND KIEL

HOLDING: FUCHS PETROLUB SE

HEADQUARTERS: Mannheim

TRUE LUBRICANT SPECIALIST: 100 % focus on lubricants

FULL LINE OF PRODUCTS:
More than 2,000 products and 6,000 product-pack combinations

CERTIFIED BY: DIN EN ISO 9001:2008,
ISO/TS 16949:2009, DIN EN ISO 14001:2004
BS OHSAS 18001:2007, KTA 1401

For more than 80 years, we have been concentrating all our activities and research efforts on the development of innovative lubricants. This specialization means that we are enjoying continuous growth – geographically, technically and in the number of application areas.

Today, FUCHS is a company that offers powerful lubricants and associated specialties worldwide in practically all areas of application and industries.

What makes our products more valuable: We develop lubricants on an application-specific basis and tailored to our partners' processes. Together, we look for the best lubricant for our customers. This type of collaboration is unique in its form, scope and intensity.

We call it a development partnership. This ability is based on one key feature: As a true lubricant specialist with our headquarters in Mannheim /Germany, we are the largest independent lubricant specialist, and this independence makes all the difference. We are open to new methods and visionary approaches – a prerequisite for innovations. And innovations are a FUCHS trademark.

OUR LUBRICANTS KEEP THE WORLD MOVING



Volkswagen Group Award 2014




- _ Leading competence in automotive lubricants.
- _ Complete range of lubricants for all automotive applications.
- _ Groundbreaking XTL® technology.



Groundbreaking XTL® technology.

While starting, engine oils with XTL® technology reach faster and easier the parts of an engine, which urgently require a protective oil film – even under extreme conditions and over the entire duration of the oil change interval.

This means: Easier start-ups, less wear and lower fuel consumption. Even oil consumption is significantly lower than with conventional SAE 5W-30 oils.



XTL®
TECHNOLOGY





Product overview

Automotive Lubricants



1_Engine Oils | **TTAN**

Engine Oils for Passenger Cars	Page 8 to 11
Racing Engine Oils; Engine Oils for Passenger Cars with Gas Engines	Page 11
Engine Oils for Mixed Fleets	Page 12
Engine Oils for Commercial Vehicles	Page 13 and 14
Engine Oils for Commercial Vehicles with Gas Engines	Page 15
Monograde Engine Oils	Page 16
Gas Engine Oils	Page 17 and 18
4-Stroke MARINE Engine Oils; 2-Stroke MARINE Engine Oils; Railroad Engine Oils; 2-Stroke Engine Oils	Page 19

2_Transmission Fluids | **TTAN**

Gear Oils for Passenger Cars	Page 20
Gear Oils for Passenger Cars and Commercial Vehicles	Page 21
Gear Oils for Commercial Vehicles	Page 22 and 23
Multifunctional Gear Oils for Construction Machinery	Page 24
Double Clutch Transmission Fluids (DCTF)	Page 25
Automatic Transmission Fluids (ATF)	Page 25 to 26

3_Hydraulic Fluids | **TTAN**

Page 28

4_Lubricants for Agricultural Machinery | **AGRIFARM**

STOU Oils	Page 29 and 30
Engine Oils	Page 31
UTTO Oils	Page 32
Gear Oils, Chain Saw Oil, Milking Machine Oil	Page 33

5_Motorcycle Lubricants | **Siikolene**

RACE	Page 34
RIDE, QUADS ATV, SCOOT	Page 35
MAINTAIN	Page 36 and 37

6_Service Products | **MAINTAIN**

Brake Fluids, Antifreeze	Page 38 and 39
Washer Fluid Additive, Diesel Fuel Additive	Page 40

7_Specialties

Page 41

8_Greases | **RENOLIT**

Page 42 and 43

9_Rapidly Biodegradable Lubricants | **PLANTO**

Page 44 and 45



1_ENGINE OILS



TITAN

Engine Oils for Passenger Cars	Specifications	Approvals	FUCHS Recommendations
<p>TITAN GT1 EVO SAE 0W-20</p> <p>XTL[®] TECHNOLOGY</p>	<p>Premium Performance Engine Oil with new XTL[®]-Technology in path-breaking viscosity class. Specially designed for highly stressed downsized engines with maximum power output, for extreme fuel-economy characteristics and reduced CO₂ emissions. Excellent cold starting behaviour, very fast oil circulation and outstanding performance reserves.</p>	<p>ACEA A1/B1</p>	<p>BMW LONGLIFE-14 FE+</p> <p>TOYOTA HONDA</p>
<p>TITAN GT1 PRO V SAE 0W-20</p> <p>XTL[®] TECHNOLOGY</p> <p>NEW</p>	<p>Premium Performance Engine Oil with new XTL[®]-Technology in ground-breaking viscosity class. Specially designed for modern VOLVO vehicles, for extreme fuel-economy characteristics and reduced CO₂ emissions. Excellent cold starting behaviour, very fast oil circulation and outstanding performance reserves.</p>		<p>VOLVO VCC RBS0-2AE</p>
<p>TITAN GT1 SAE 0W-20</p> <p>XTL[®] TECHNOLOGY</p>	<p>Premium Performance Engine Oil with new XTL[®]-Technology in path-breaking viscosity class and globally unique Zinc-free Additive Technology, for high performance cars with gasoline and diesel engines. Specially designed for sportive driving and maximum power output. Extreme fuel-economy characteristics. Excellent cold starting behaviour. Outstanding performance reserves.</p>		<p>ACEA C2 API SL ILSAC GF-4</p>
<p>TITAN GT1 PRO FLEX SAE 5W-30</p> <p>XTL[®] TECHNOLOGY</p>	<p>Premium Performance, extreme fuel-economy engine oil with new XTL[®]-Technology for optimum cold start ability and outstanding performance reserves. For modern passenger cars and light commercial vehicles with or without extended service intervals. Specially developed for BMW, Mercedes-Benz and Opel vehicles with exhaust after treatment and turbocharger.</p>	<p>ACEA C3 API SN/SM</p>	<p>BMW LONGLIFE-04 dexos2[™] (GB2C0209075) MB-APPROVAL 229.51 MB-APPROVAL 229.52 VW 502 00/ 505 00/ 505 01</p> <p>FIAT 9.55535-S3 FORD M2C917-A GM-LL-A-025 GM-LL-B-025</p>
<p>TITAN GT1 PRO C-3 SAE 5W-30</p> <p>XTL[®] TECHNOLOGY</p>	<p>Premium Performance, extreme fuel-economy engine oil with new XTL[®]-Technology for optimum cold start ability and outstanding performance reserves. For modern passenger cars and light commercial vehicles with or without extended service intervals. Specially developed for BMW-, VW and Mercedes-Benz vehicles with exhaust after treatment and turbocharger.</p>	<p>ACEA C3</p>	<p>BMW LONGLIFE-04 MB-APPROVAL 229.51 PORSCHE C30 VW 504 00/ 507 00</p> <p>FIAT 9.55535-S3 FORD M2C917-A</p>
<p>TITAN GT1 SAE 5W-40</p> <p>XTL[®] TECHNOLOGY</p>	<p>Premium Performance, fuel-economy engine oil with new XTL[®]-Technology for optimum cold start ability and outstanding performance reserves. For modern passenger cars and light commercial vehicles with or without extended service intervals. Specially developed for vehicles with exhaust after treatment and turbocharger.</p>	<p>ACEA C3 API SN/SM/CF FORD M2C917-A</p>	<p>BMW LONGLIFE-04 MB-APPROVAL 226.5 MB-APPROVAL 229.31 PORSCHE A40 RENAULT RN0700/ RN0710 VW 502 00 / 505 00 / 505 01</p> <p>FIAT 9.55535-S2</p>

1_ENGINE OILS



TITAN

Engine Oils for Passenger Cars	Specifications	Approvals	FUCHS Recommendations
TITAN GT1 SAE 0W-30 NEW	Premium Performance, fuel-economy engine oil for modern passenger cars and light commercial vehicles. Specially developed for latest PSA gasoline and diesel vehicles with exhaust after treatment and turbocharger. Excellent cold starting, lower oil consumption and minimized exhaust emissions.	ACEA C2	PSA B71 2312 FIAT 9.55535-DS1/GS1 IVECO 18-1811 CLASSE SC1 LV
TITAN GT1 PRO C-1 SAE 5W-30	Premium Performance, extreme fuel-economy engine oil for modern passenger cars and light commercial vehicles with or without extended service intervals. Specially developed for vehicles with exhaust after treatment and turbocharger. Optimum cold starting, lower oil consumption and minimized exhaust emissions.	ACEA C1	JASO DL-1 FORD WSS-M2C934-B MAZDA
TITAN GT1 PRO C-2 SAE 5W-30	Premium Performance, extreme fuel-economy engine oil for modern passenger cars and light commercial vehicles with or without extended service intervals. Specially developed for PSA vehicles with exhaust after treatment and turbocharger. Optimum cold starting, lower oil consumption and minimized exhaust emissions.	ACEA C2 API SN/SM/CF	PSA B71 2290 FIAT 9.55535-S1 HONDA IVECO 18-1811 CLASSE SC1 MAZDA SUBARU SUZUKI TOYOTA
TITAN GT1 PRO C-4 SAE 5W-30	Premium Performance, extreme fuel-economy engine oil for modern passenger cars and light commercial vehicles with or without extended service intervals. Specially for Renault vehicles with exhaust after treatment and turbocharger. Optimum cold starting, lower oil consumption and minimized exhaust emissions.	ACEA C4	MB-APPROVAL 226.51 RENAULT RN0720
TITAN GT1 PRO B-Tec SAE 5W-30 XTL[®] <small>TECHNOLOGY</small>	Premium Performance, extreme fuel-economy engine oil with new XTL [®] -Technology for modern passenger cars and light commercial vehicles with or without extended service intervals. Specially for Mercedes-Diesel-Vehicles with exhaust after treatment and turbocharger. Optimum cold starting, lower oil consumption and minimized exhaust emissions.	ACEA C2/C3 API SN	MB-APPROVAL 229.52
TITAN Supersyn LONGLIFE PLUS SAE 0W-30	Ultra High Performance, extreme fuel-economy engine oil formulated with fully synthetic base oil for VW engines. Specially developed for VW Longlife Technology. For all passenger car gasoline and diesel engines with or without pump injector technology. Excellent cold starting and lower oil consumption.		VW 503 00/506 00/506 01 ACEA A5/B5 BMW LONGLIFE 01-FE
TITAN Supersyn LONGLIFE SAE 0W-30	Ultra High Performance, extreme fuel-economy engine oil for a variety of vehicles with or without extended service intervals. Excellent cold starting and lower oil consumption.	ACEA A3/B4 API SL	MB-APPROVAL 229.5 BMW LONGLIFE-01

1_ENGINE OILS



TITAN

Engine Oils for Passenger Cars		Specifications	Approvals	FUCHS Recommendations
TITAN Supersyn LONGLIFE SAE 0W-40	Ultra High Performance, fuel-economy engine oil for a variety of vehicles with or without extended service intervals. Excellent cold starting and lower oil consumption.	ACEA A3/B4 API SN	MB-APPROVAL 229.5 PORSCHE A40 VW 502 00/505 00	AMG ASTON-MARTIN BMW LONGLIFE-01 FORD M2C937-A
TITAN Supersyn LONGLIFE SAE 5W-40	Ultra High Performance, fuel-economy engine oil for a variety of vehicles with or without extended service intervals. Optimum cold starting and lower oil consumption.	ACEA A3/B4 API SN/SM/CF	BMW LONGLIFE-01 MB-APPROVAL 226.5 MB-APPROVAL 229.5 PORSCHE A40 RENAULT RN0700/ RN0710 VW 502 00/ 505 00	GM-LL-B-025 HYUNDAI PSA B71 2296
TITAN Supersyn FE SAE 0W-30 NEW	Ultra High Performance, fuel-economy engine oil for a variety of vehicles with or without extended service intervals. Excellent cold starting properties and low oil consumption.	ACEA A5/B5	VOLVO VCC 95200377	RENAULT RN 0700
TITAN Supersyn SAE 5W-30	Ultra High Performance, extreme fuel-economy engine oil for a variety of vehicles with or without extended service intervals. Optimum cold starting and lower oil consumption.	ACEA A3/B4 API SL/CF	MB-APPROVAL 229.3 VW 502 00/505 00	BMW LONGLIFE-98 GM-LL-A-025 GM-LL-B-025 RENAULT RN0700/ RN0710
TITAN Supersyn F Eco-B SAE 5W-20	Ultra High Performance, extreme fuel-economy engine oil especially developed for Ford EcoBoost gasoline engines. Optimum cold starting and lower oil consumption.	ACEA A1/B1 API SN	FORD M2C948-B	CHRYSLER MS 6395 FORD M2C925-A FORD M2C925-B
TITAN Supersyn F Eco-DT SAE 5W-30	Ultra High Performance, extreme fuel-economy engine oil especially suitable for Ford DuraTorq-Diesel engines. Optimum cold starting and lower oil consumption.	ACEA A1/B1 ACEA A5/B5 API SL/CF FORD M2C913-C	FORD M2C913-D	CHRYSLER MS 6395 FORD M2C913-A FORD M2C913-B IVECO 18-1811 CLASSE S1/S2 JAGUAR M2C913-B RENAULT RN0700
TITAN Supersyn SAE 5W-40	Ultra High Performance, fuel-economy engine oil for a variety of vehicles with or without extended service intervals. Optimum cold starting and lower oil consumption.	ACEA A3/B4 API SN/SM/CF	MB-APPROVAL 229.3 PORSCHE A40 RENAULT RN0700/ RN0710 VW 502 00/505 00	BMW LONGLIFE-98 FIAT 9.55535-H2/M2/N2/ Z2 GM-LL-A-025 GM-LL-B-025
TITAN Supersyn SAE 5W-50	Ultra High Performance, fuel-economy engine oil for passenger cars. Optimum cold starting behaviour and low oil consumption. Highly durable lubricating film and high oil pressure.			ACEA A3/B4 API SL/CF
TITAN Supersyn SAE 10W-60	Ultra High Performance, fuel-economy engine oil for passenger cars. Low oil consumption. Highly durable lubricating film and high oil pressure.			ACEA A3/B3 API SL/CF FIAT 9.55535-H3
TITAN SYN MC SAE 10W-40	Super High Performance, fuel-economy engine oil based on MC-synthesis for a variety of gasoline and diesel engines in passenger cars. Lower oil consumption.	ACEA A3/B4 API SL/CF	MB-APPROVAL 229.1	BMW SPECIAL FIAT 9.55535-D2/G2 MAZDA VW 500 00/505 00

1_ENGINE OILS



TITAN

Engine Oils for Passenger Cars		Specifications	Approvals	FUCHS Recommendations
TITAN SYN SN SAE 0W-20 NEW	Super High Performance, fuel-economy engine oil for a variety of gasoline engines in passenger cars. Good cold starting behaviour and low oil consumption.	API SN ILSAC GF-5		
TITAN FORMULA SAE 15W-40	High Performance Engine Oil specially for all normally aspirated and turbocharged gasoline and diesel engines in passenger cars operated under normal conditions.	API SL/CG-4	MB-APPROVAL 229.1	ACEA A3/B3/B4 FIAT 9.55535-D2/G2 VW 501 01/505 00

Racing Engine Oils		Specifications	Approvals	FUCHS Recommendations
TITAN RACE SAE 5W-30	Premium Racing Engine Oil for Race cars with Gasoline or Diesel engines. Especially developed for professional use in racing applications. Combines optimum protection with power increase and reduced fuel consumption due to minimized frictional losses.			ACEA C3
TITAN RACE SAE 10W-60	Premium Racing Engine Oil for Race cars fuelled with Gasoline or Diesel engines. Especially developed for professional use in racing applications. Offers optimum protection due to minimized frictional losses and a stable oil film.			ACEA A3/B3 API SL/CF

Engine Oils for Passenger Cars with Gas Engines		Specifications	Approvals	FUCHS Recommendations
TITAN GT1 PRO GAS SAE 5W-30	Premium Performance Gas Engine Oil for modern passenger cars and light commercial vehicles. Specially for gasoline engines with LPG- and CNG operation. Optimum engine cleanness, lower oil consumption and minimized exhaust emissions.	ACEA C3 API SM	BMW LONGLIFE-04 dexos2™ (GB2C0209075) MB-APPROVAL 229.51 VW 502 00	CHEVROLET FIAT 9.55535-G1 OPEL
TITAN GT1 PRO GAS SAE 5W-40	Premium Performance Gas Engine Oil for modern passenger cars and light commercial vehicles. Specially for gasoline engines with LPG- and CNG operation. Optimum engine cleanness, lower oil consumption and minimized exhaust emissions.	ACEA C3 API SM	BMW LONGLIFE-04 MB-APPROVAL 229.31 VW 502 00 / 505 00 / 505 01	CITROËN FIAT 9.55535-H2/ N2/M2/S2/Z2 FORD PEUGEOT RENAULT
TITAN SYN PRO GAS SAE 10W-40	Super High Performance Gas Engine Oil for passenger cars and light commercial vehicles. Specially developed for gas engines with LPG- and CNG operation.	ACEA A3/B4 API SL	MB-APPROVAL 229.1	BMW SPECIAL CHEVROLET FIAT 9.55535-G2 VW 500 00

1_ENGINE OILS



TITAN

Engine Oils for Mixed Fleets		Specifications	Approvals	FUCHS Recommendations
<p>TITAN UNIMAX ULTRA MC SAE 10W-40</p>	<p>Premium Performance Engine Oil based on MC-synthesis for all commercial vehicles, off-highway equipment and passenger cars. Substantial rationalisation opportunities for mixed fleets. Prolongation of drain intervals possible with many manufacturers. Good cold starting and lower oil consumption.</p>	<p>ACEA E7/B4/B3/A3 API CI-4 GLOBAL DHD-1 JASO DH-1</p>	<p>CUMMINS CES 20077/8 DETROIT DIESEL 93K215 DEUTZ DQC III-10 MACK EO-M PLUS MAN M 3275-1 MB-APPROVAL 228.3 MB-APPROVAL 229.1 MB-APPROVAL 235.27 MTU DDC TYPE-2 RENAULT RLD / RLD-2 VOITH-RETARDER „A“ VOLVO VDS-3</p>	<p>ALLISON C-4 CAT ECF-2 CUMMINS CES 20071/2/6 DAF VW 500 00/ 501 01/505 00</p>
<p>TITAN UNIMAX PLUS MC SAE 10W-40</p>	<p>Ultra High Performance, fuel-economy engine oil based on MC-synthesis for all commercial vehicles, off-highway equipment and passenger cars. Substantial rationalisation opportunities for mixed fleets. Prolongation of drain intervals possible with some manufacturers. Good cold starting and lower oil consumption.</p>	<p>ACEA E7/B3/A3 API CH-4</p>	<p>CUMMINS CES 20077 DEUTZ DQC II-10 MAN M 3275-1 MB-APPROVAL 228.3 MB-APPROVAL 229.1 MB-APPROVAL 235.27 MTU DDC TYPE 2 RENAULT RD / RD-2 VOITH-RETARDER „A“ VOLVO VDS-2</p>	<p>ALLISON C-4 CUMMINS CES 20071/2/6 DAF MACK EO-M PLUS SCANIA</p>
<p>TITAN UNIVERSAL HD SAE 15W-40</p>	<p>High Performance Engine Oil for mixed fleets operated under normal conditions. Good performance in normally aspirated and turbocharged diesel engines.</p>	<p>ACEA A3/B3/B4 API CG-4/CF/SL</p>	<p>DEUTZ DQC I-02 MAN 271 MB-APPROVAL 228.1 MB-APPROVAL 229.1 MTU DDC TYPE 2</p>	<p>ACEA E2 MIL-L-2104 E ALLISON C-4 CASE MS 1120 DAF MACK EO-L NH 330G SCANIA STEYR A-202 VOLVO VDS VW 501 01/505 00</p>

1_ENGINE OILS



TITAN

Engine Oils for Commercial Vehicles		Specifications	Approvals	FUCHS Recommendations
TITAN CARGO MAXX SAE 5W-30 	<p>Premium MAXX Performance Engine Oil with new XTL®-Technology. Specially developed for vehicles with modern exhaust after treatment and turbocharger. Optimum cold starting properties and ageing stability for extreme fuel-economy over the whole drain-interval.</p>	ACEA E6	DEUTZ DQC IV-10 LA MACK EO-N MAN M 3477 MB-APPROVAL 228.51 MTU DDC TYPE 3.1 RENAULT RXD/RLD-2 VOLVO VDS-3	ACEA E7 IVECO 18-1804 CLASSE TLS E6
TITAN CARGO MAXX SAE 10W-40 	<p>Premium MAXX Performance Engine Oil with new XTL®-Technology. Specially developed for vehicles with modern exhaust after treatment and turbocharger. Good cold starting properties and ageing stability for fuel-economy over the whole drain-interval.</p>	ACEA E9/E7/E6 API CI-4 CAT ECF-1-a JASO DH-2	DEUTZ DQC IV-10 LA MACK EO-M PLUS MACK EO-N MAN M 3271-1 MAN M 3477 MB-APPROVAL 228.51 MB-APPROVAL 235.28 MTU DDC TYPE 3.1 RENAULT RXD/RGD/ RLD-2 SCANIA LA VOITH-RETARDER „B“ VOLVO VDS-3 / CNG	CUMMINS CES 20077 DAF IVECO 18-1804 CLASSE TLS E9 MAN M 3277 CRT
TITAN CARGO SL SAE 5W-30	<p>Ultra High Performance, extreme fuel-economy engine oil for a variety of commercial vehicle diesel engines, with optimum cold starting and lower oil consumption. Specially developed for extended service intervals.</p>	ACEA E7/E4	CUMMINS CES 20077 DEUTZ DQC IV-10 FORD WSS-M2C212-A1 MACK EO-N MAN M 3277 MB-APPROVAL 228.5 MTU DDC TYPE 3 RENAULT RXD/RLD-2 SCANIA LDF-3 VOLVO VDS-3	DAF IVECO 18-1804 CLASSE TFE
TITAN CARGO LD3 SAE 10W-40	<p>Ultra High Performance, fuel-economy engine oil for use in SCANIA Euro 6 vehicles. Specially developed for extended service intervals.</p>	ACEA E7/E4 API CF	MAN M 3277 MB-APPROVAL 228.5 SCANIA LDF-3	
TITAN CARGO MC SAE 10W-40	<p>Ultra High Performance, fuel-economy engine oil based on MC-synthesis for a variety of commercial vehicle diesel engines. Specially developed for extended service intervals. Good cold starting and lower oil consumption.</p>	ACEA E7/E4 API CI-4 GLOBAL DHD-1	CUMMINS CES 20077/8 DETROIT DIESEL 93K215 DEUTZ DQC III-10 MACK EO-M PLUS MACK EO-N MAN M 3277 MB-APPROVAL 228.5 MTU DDC TYPE 3 RENAULT RXD/RLD-2 SCANIA LDF-2 VOLVO VDS-3	DAF IVECO 18-1804 SDFG OM-1901A

1_ENGINE OILS



TITAN

Engine Oils for Commercial Vehicles	Specifications	Approvals	FUCHS Recommendations	
<p>TITAN CARGO EU6 SAE 5W-30</p> <p>NEW</p>	<p>Ultra High Performance, fuel-economy engine oil for use in many OEM Euro 6 engines fitted with modern exhaust after treatment devices. Excellent cold starting properties and low oil consumption.</p>	<p>ACEA E9/E7/E6 API CJ-4 CAT ECF-3 JASO DH-2</p>	<p>CUMMINS CES 20081 DEUTZ DQC IV-10 LA MACK EO-0 PREMIUM PLUS MAN M 3677 MB-APPROVAL 228.51 MTU DDC TYPE 3.1 RENAULT RLD-3 SCANIA LA VOLVO VDS-4</p>	<p>DETROIT DIESEL 93K218 IVECO 18-1804 CLASSE TLS E6 MAN M 3271-1</p>
<p>TITAN CARGO SAE 5W-40</p>	<p>Ultra High Performance, fuel-economy engine oil, specially developed for commercial vehicle diesel engines with extended service intervals, exhaust after treatment and turbocharger.</p>	<p>ACEA E9/E7 API CJ-4 CAT ECF-2/ECF-3</p>	<p>CUMMINS CES 20081 DETROIT DIESEL 93K218 DEUTZ DQC II-10 LA FAWDE Q/XC 3135-2007 MACK EO-0 PREMIUM PLUS MAN M 3575 MB-APPROVAL 228.31 RENAULT RLD-3 VOLVO VDS-4</p>	<p>DETROIT DIESEL 93K214 93K215</p>
<p>TITAN CARGO SAE 10W-30</p>	<p>Ultra High Performance, fuel-economy engine oil, specially developed for commercial vehicle diesel engines with extended service intervals, exhaust after treatment and turbocharger.</p>	<p>ACEA E9 API CJ-4 CAT ECF-1a/ ECF-2/ ECF-3</p>	<p>DEUTZ DQC III-10LA MACK EO-0 PREMIUM PLUS MAN 3575 MB-APPROVAL 228.31 RENAULT RLD-3 VOLVO VDS-4</p>	<p>CUMMINS 20081 MTU DDC TYPE 2.1</p>
<p>TITAN CARGO SAE 15W-40</p>	<p>Ultra High Performance, fuel-economy engine oil for a variety of commercial vehicle diesel engines. Specially developed for Volvo with extended service intervals, exhaust after treatment and turbocharger.</p>	<p>ACEA E9/E7 API CJ-4/CI-4 PLUS/CI-4 CAT ECF-2/ECF-3</p>	<p>CUMMINS CES 20081 DEUTZ DQC III-10 LA DETROIT DIESEL 93K218 FAWDE Q/XC 3135-2007 MACK EO-0 PREMIUM PLUS MAN M 3275-1 MAN M 3575 MB-APPROVAL 228.31 MTU DDC TYPE 2.1 RENAULT RLD-3 VOLVO VDS-4</p>	<p>ALLISON C-4</p>
<p>TITAN TRUCK PLUS SAE 15W-40</p>	<p>Super High Performance Engine Oil for a variety of diesel and gasoline engines. Specially for highly-loaded commercial vehicle diesel engines. Lower oil consumption.</p>	<p>ACEA E7 API CI-4/SL GLOBAL DHD-1 CAT ECF-1a/ECF-2</p>	<p>CUMMINS CES 20076/7/8 DETROIT DIESEL 93K215 DEUTZ DQC III-10 MACK EO-N MAN M 3275-1 MB-APPROVAL 228.3 MTU DDC TYPE 2 RENAULT RLD/RLD-2 VOLVO VDS-3</p>	<p>ALLISON C-4 CAT TO-2 CASE MS 1121 CUMMINS CES 20071/2 IVECO 18-1804 CLASSE T2 E7 NH 330H</p>

1_ENGINE OILS



TITAN

Engine Oils for Commercial Vehicles with Gas Engines	Specifications	Approvals	FUCHS Recommendations
<p>TITAN TRUCK SAE 15W-40</p>	<p>Super High Performance Engine Oil for a variety of diesel engines. Specially for highly-loaded commercial vehicle diesel engines. Lower oil consumption.</p>	<p>ACEA E7 API CH-4/SJ CAT ECF-1-a</p>	<p>CUMMINS CES 20076/7 DEUTZ DQC II-10 MACK EO-N MAN M 3275-1 MB-APPROVAL 228.3 MTU DDC TYPE 2 RENAULT RLD/RLD-2 VOLVO VDS-3</p>
<p>TITAN CARGO PRO GAS SAE 5W-30</p>	<p>Premium Performance, zinc-free, extreme fuel-economy engine oil for highly-supercharged commercial vehicle gas engines as well as diesel engines with exhaust gas after treatment systems. Specially developed for gas powered engines with and without turbocharger. Optimum cold starting, lower oil consumption and minimized exhaust emissions. For MAN gas engines extended drain intervals are possible depending on engine type.</p>	<p>ACEA E6</p>	<p>MAN M 3271-1 MAN M 3271-3 MAN M 3477 MB-APPROVAL 226.9 MB-APPROVAL 235.28 VOITH-RETARDER „B“</p>

1_ENGINE OILS



TITAN

Monograde Engine Oils		Specifications	Approvals	FUCHS Recommendations
TITAN UNIVERSAL HD SAE 10W	High Performance Monograde Engine Oil for gasoline and diesel engines. Specially developed for off-road vehicles. Depending upon manufacturer regulation also in other aggregates applicable.	ACEA E2 API CF-4/SG	MAN 270 MB-APPROVAL 228.0 ZF TE-ML 03B	MIL-L-2104 D ALLISON C-4 CAT TO-2 ZF TE-ML 02C
TITAN UNIVERSAL HD SAE 20W-20	High Performance Monograde Engine Oil for gasoline and diesel engines. Specially developed for off-road vehicles. Depending upon manufacturer regulation also in other aggregates applicable.	ACEA E2 API CF-4/SG	MAN 270 MB-APPROVAL 228.0 MB-APPROVAL 235.27 VOITH-RETARDER „A“	MIL-L-2104 D ALLISON C-4 CAT TO-2 ZF TE-ML 02C
TITAN UNIVERSAL HD SAE 30	High Performance Monograde Engine Oil for gasoline and diesel engines. Specially developed for off-road vehicles. Depending upon manufacturer regulation also in other aggregates applicable.	ACEA E2 API CF-4/SG	DEUTZ DQC I-02 MAN 270 MB-APPROVAL 228.2 MTU DDC TYPE 2 ZF TE-ML 04B	MIL-L-2104 D ALLISON C-4 CAT TO-2 ZF TE-ML 02C
TITAN UNIVERSAL HD SAE 40	High Performance Monograde Engine Oil for gasoline and diesel engines. Specially developed for off-road vehicles. Depending upon manufacturer regulation also in other aggregates applicable.	ACEA E2 API CF-4/SG	DEUTZ DQC I-02 MAN 270 MB-APPROVAL 228.2 MB-APPROVAL 235.12 MTU DDC TYPE 2 ZF TE-ML 04B	API CF-2 MIL-L-2104 D ALLISON C-4 CAT TO-2 ZF TE-ML 02C
TITAN UNIVERSAL HD SAE 50	High Performance Monograde Engine Oil for gasoline and diesel engines. Specially developed for off-road vehicles. Depending upon manufacturer regulation also in other aggregates applicable.	ACEA E2 API CF-4/SG	DEUTZ DQC I-02 MAN M 3275-2 MB-APPROVAL 228.0	MIL-L-2104 D ALLISON C-4 CAT TO-2 ZF TE-ML 02C
TITAN UNIVERSAL HD SAE 30 MTU	High Performance dedicated break in engine oil for MTU diesel and gas engines, developed to improve operating characteristics with enhanced corrosion protection.		MTU DDC TYPE 1	
TITAN UNIVERSAL HD SAE 30 ZF	High Performance Monograde Engine Oil especially for initial fill of ZF-transmissions.		ZF TE-ML 02H, 04B	ACEA E2 API CF MAN 270 MB 228.0 MTU DDC TYPE 1

1_ENGINE OILS



TITAN

Gas Engine Oils	Specifications	Approvals	FUCHS Recommendations
TITAN GANYMET ULTRA	Premium Performance Engine Oil, zinc-free, for stationary gas engines.	2G TA-003 agenitor series 2,3 AGROGEN CAT CG132, CG170, CG260 JENBACHER TA 1000-1109 - A, CAT: series 2, 3, 4 (Version B), 6 (Version C, E) - B, CAT: series 2, 3 MAN M 3271-4 MTU Onsite Energy DK-BS-0001 (E, P, B) MTU Onsite Energy DK-BS-0002 (B) MWM TR 0199-99-02105 (DEUTZ POWER SYSTEMS) SEVA TRS-07 SPANNER RE ² TEDOM 61-0-0281.1/L, B, S	
TITAN GANYMET PLUS	Super High Performance Engine Oil, zinc-free, for stationary gas engines.	CAT CG132, CG170, CG260 DREYER & BOSSE JENBACHER TA 1000-1109 - B: series 2, 3 MTU Onsite Energy DK-BS-0001 (B) MWM TR 0199-99-02105 (DEUTZ POWER SYSTEMS) SEVA TRS-07	
TITAN GANYMET PLUS LA	„Low Ash“ Super High Performance Engine Oil, zinc-free, for stationary gas engines.	CAT CG132, CG170, CG260 DEUTZ TR 0199-99-01213 MWM TR 0199-99-02105 (DEUTZ POWER SYSTEMS) SEVA TRS-07 TEDOM 61-0-0281.1/G, P	CATERPILLAR CUMMINS WAUKESHA
TITAN GANYMET	High Performance Engine Oil for stationary gas engines.	ASJA AMBIENTE ITALIA JENBACHER TA 1000-1109 - C: series 2, 3 MAN M 3271-4 MTU Onsite Energy DK-BS-0001 (B,K) SEVA TRS-07	

1_ENGINE OILS



TITAN

Gas Engine Oils	Specifications	Approvals	FUCHS Recommendations
<p>TITAN GANYMET LA</p>	<p>„Low Ash“ High Performance Engine Oil for stationary gas engines.</p>	<p>CAT CG132, CG170, CG260 DEUTZ TR 0199-99-01213 JENBACHER TA 1000-1109 - A, CAT: series 2, 3, 4 (Version B), 6 (Version C, E) MAN M 3271-2 MTU Onsite Energy DK-BS-0001 (E, P, K) MWM TR 0199-99-02105 (DEUTZ POWER SYSTEMS) SEVA TRS-07</p>	<p>CATERPILLAR CUMMINS WAUKESHA</p>

1_ENGINE OILS



TITAN

4-Stroke MARINE Engine Oils		Specifications	Approvals	FUCHS Recommendations
TITAN MARINE FC-W 10W-30	Super High Performance Engine Oil for marine leisure 4-stroke gasoline engines, in accordance with the latest requirements of NMMA.		NMMA FC-W	BOMBARDIER EVINRUDE, HONDA JOHNSON MERCURY SEADOO SUZUKI YAMAHA

2-Stroke MARINE Engine Oils		Specifications	Approvals	FUCHS Recommendations
TITAN MARINE TC-W 3	Ultra High Performance Engine Oil for marine leisure 2-stroke engines, in accordance with the latest requirements of NMMA.		NMMA TC-W3	BOMBARDIER EVINRUDE, JOHNSON KAWASAKI MARINER MERCURY SEADOO SUZUKI TOHATSU YAMAHA

Railroad Engine Oils		Specifications	Approvals	FUCHS Recommendations
TITAN RAILGEN 13 SAE 40	High Performance Rail Locomotive Monograde Engine Oil according to API CF utilizing zinc and chlorine free additive technology.	API CD/CF	GE Generation 4LL GM - EMD GENERATION 5	LMOA GENERATION 5 CATERPILLAR 3600

2-Stroke Engine Oils		Specifications	Approvals	FUCHS Recommendations
TITAN 2T 100 S	Ultra High Performance two-stroke engine oil for Autolube and Premix systems formulated with fully synthetic base oils.	API TC JASO FD ISO L-EGD		TISI
TITAN 2T S	Super High Performance 2-stroke engine oil. Mixes rapidly. Suitable for Autolube as well as Premix systems.	API TC JASO FC ISO-L-EGC		
TITAN 2T M	High Performance 2-stroke engine oil. Mixes rapidly. Suitable for Autolube as well as Premix systems.	API TC		

2_TRANSMISSION FLUIDS



TITAN

Gear Oils for Passenger Cars		Spezifikation	Approvals	FUCHS Recommendations
TITAN SINTOFLUID FE SAE 75W	Premium Performance Manual Transmission Fluid offering increased gearbox efficiency in passenger cars due to low viscosity level. Reduces fuel consumption and offers best properties at low temperature. Suitable as fill for life fluid according to manufacturer.	API GL-4		VW TL 521 71 (G 052 171 A1/A2) VW TL 521 78 (G 052 178 A2) VW TL 525 12 (G 052 512 A2) VW TL 525 27 (G 052 527 A2) VW TL 726 (G 052 726 A2/G 055 726 A2/ G 060 726 A2/G 070 726 A2)
TITAN SINTOFLUID SAE 75W-80	Premium Performance Manual Transmission Fluid for passenger cars. Offering good gearbox efficiency. Suitable as fill for life fluid according to manufacturer.	API GL-5		MIL-L-2105 D ALFA ROMEO BMW 83 22 0 309 031 BMW 83 22 0 403 247 BMW 83 22 7 533 818 BMW 2300 1434 404 BMW 2300 7533 513 BMW 2300 7533 818 CITROËN, FIAT FORD M2C200-C/ C2/ C3 LANCIA OPEL 19 40 182, 19 40 757, 19 40 768, 19 40 776 PEUGEOT, RENAULT VOLVO 97308 VW 501 50 (G 005 000 05/ G 005 000/ G 005 000 20/ G 052 911 A1/A2)
TITAN SINTOPOID FE SAE 75W-85	Premium Performance Gear Oil offering increased gearbox efficiency in passenger cars due to low viscosity level, formulated with fully-synthetic base oils. Reduces fuel consumption and offers best properties at low temperature. Suitable as fill for life fluid according to manufacturer.	API GL-5	MB-APPROVAL 235.7 ZF TE-ML 18	ALFA ROMEO, BMW FIAT, LANCIA VW TL 521 45-X (G 052 145 A1) VW TL 521 90 (G 052 190 A2/ G 055 190 A2)
TITAN SINTOPOID SAE 75W-90	Premium Performance Axle Gear Oil for passenger cars, also for for high-offset hypoid drives offering good gearbox efficiency. Suitable as fill for life fluid according to manufacturer.	API GL-5		MIL-L-2105 D BMW VW TL 521 45-Y (G 052 145 A2)
TITAN SINTOPOID LS SAE 75W-90	Premium Performance fully-synthetic multifunctional gear oil. Suitable for axles and transfer gearboxes with or without self locking differentials and also as trouble shooter for conventional manual transmissions.	API GL-4/-5/-5 incl. LS		VW G50/G51
TITAN SINTOPOID LS SAE 75W-140	Premium Performance Gear Oil for axle and transfer gearboxes, formulated with fully-synthetic base oils. Suitable for axle and transfer gearboxes with and without limited slip differential.	API GL-5		BMW 83 22 2 282 583 BMW 83 22 9 407 870 CHRYSLER MS-8985 FORD M2C192-A GM 12346140 JOHN DEERE JDM J11G SCANIA STO 1:0

2_TRANSMISSION FLUIDS



TITAN

Gear Oils for Passenger Cars and Commercial Vehicles	Specifications	Approvals	FUCHS Recommendations
TITAN SUPERGEAR MC SAE 80W-90	Super High Performance Gear Oil based on MC-Synthesis for extended oil change intervals.	API GL-4/GL-5 SCANIA STO 1:0	MAN 341 TYPE E2 MAN 341 TYPE Z2 MAN 342 TYPE M2 MB-APPROVAL 235.0 ZF TE-ML 02B, 05A, 12L, 12M, 16B, 17B, 19B, 21A
TITAN SUPERGEAR MC SAE 80W-140	Super High Performance Gear Oil based on MC-Synthesis for extended oil change intervals.	API GL-4/GL-5 SCANIA STO 1:0	JOHN DEERE JDM J11E OPEL 19 42 386 RENAULT VI VOLVO 97310 ZF TE-ML 08
TITAN SUPERGEAR SAE 80W-90	High Performance Gear Oil for extended oil change intervals.	API GL-4/GL-5	MAN 342 TYPE M2 ZF TE-ML 05A, 12E, 17B, 19B, 21A
TITAN SUPERGEAR SAE 85W-140	High Performance Gear Oil for extended oil change intervals.	API GL-4/GL-5	ZF TE-ML 05A, 12E, 16D, 21A
TITAN GEAR LS SAE 90	High Performance LS (Limited Slip) hypoid gear oil for axles with or without limited slip differentials.	API GL-5	ZF TE-ML 05C, 12C, 16E, 21C
TITAN GEAR MP SAE 80	High Performance Gear Oil for synchronized and non-synchronized manual gearboxes as well as auxiliary drives, axles and differentials in commercial vehicles and passenger cars.	API GL-4	MAN 341 TYPE E1 MAN 341 TYPE Z2 MB-APPROVAL 235.1 ZF TE-ML 17A
TITAN GEAR MP SAE 90	High Performance Gear Oil for synchronized and non-synchronized manual gearboxes as well as auxiliary drives, axles and differentials in commercial vehicles and passenger cars.	API GL-4	MAN 341 TYPE Z1
TITAN GEAR HYP SAE 90	High Performance Gear Oil for highly-stressed differentials in commercial vehicles and passenger cars.	API GL-5	MAN 342 TYPE M1 MB-APPROVAL 235.0 ZF TE-ML 16C, 17B, 19B, 21A
			FORD M2C9102-A JOHN DEERE JDM J11E OPEL 19 42 387 VOLVO 97310 VW TL 727 ZF TE-ML 07, 08

2_TRANSMISSION FLUIDS



TITAN

Gear Oils for Commercial Vehicles		Specifications	Approvals	FUCHS Recommendations
TITAN CYTRAC SL SAE 75W-90	Premium Performance Gear Oil for highly-stressed hypoid axles in commercial vehicles formulated with fully-synthetic base oils. Developed for the longest oil change intervals in commercial vehicle axle drives.	API GL-5 SCANIA STO 1:0	MAN 342 TYPE S1	JOHN DEERE JDM J11E JOHN DEERE JDM J11G MB 235.8 VOLVO 97312 ZF TE-ML 05B, 07, 08, 12B, 16F, 17B
TITAN CYTRAC RR SAE 75W-90	Fully synthetic Premium Performance Hypoid Gear Oil for axle drives in railcars and heavy duty vehicles.	API GL-5 API MT-1 SCANIA STO 1:0	SAE J2360 SIEMENS FLENDER Gear Units for Railway Vehicles VOITH TURBO 132.00374401 (3.325-340) VOITH TURBO 132.00374402 (3.325-342) ZF TE-ML 05B, 12L, 12N, 16F, 17B, 19C, 21B	Gmeinder Getriebebau railway applications
TITAN CYTRAC MB SYNTH SAE 75W-90	Premium Performance Gear Oil for extended drain intervals in commercial vehicles, specially developed for Mercedes-Benz Actros vehicles, formulated with fully-synthetic base oils. Reduces fuel consumption by improving gearbox efficiency. Suitable for the longest oil change intervals.	API GL-4	MAN 341 TYPE MB MB-APPROVAL 235.11	ZF TE-ML 08
TITAN CYTRAC ULTRA SYNTH SAE 75W-80	Premium Performance Gear Oil for extended drain intervals in commercial vehicles, especially developed for ZF heavy duty transmissions with and without Intarder. Reduces fuel consumption by improving gearbox efficiency. Suitable for longest oil change intervals.	API GL-4 VOLVO 97307	MAN 341 TYPE Z5 ZF TE-ML 01E, 02E, 16P	DAF IVECO MAN RENAULT TRUCKS
TITAN CYTRAC MAN SYNTH SAE 75W-80	Premium Performance Gear Oil for extended drain intervals in commercial vehicles manual gearboxes, specially developed for manual and automatic ZF-gearboxes, formulated with fully-synthetic base oils. Reduces fuel consumption by improving gearbox efficiency. Suitable for the longest oil change intervals and compatible with Carbon-Synchronizers.	API GL-4	MAN 341 TYPE Z4 ZF TE-ML 01L, 02L, 16K	DAF EATON IVECO RENAULT VOLVO 97307
TITAN CYTRAC LD SAE 75W-80	Ultra High Performance Gear Oil for extended oil change intervals in commercial vehicles fitted with integral intarders or supplementary retarders.	API GL-4	EATON MAN 341 TYPE E3	DAF MAN 341 TYPE Z3 VOLVO 97305 ZF TE-ML 02D, 08
TITAN CYTRAC HSY SAE 75W-90	Ultra High Performance Gear Oil for commercial vehicle manual transmissions and axle drives formulated with fully-synthetic base oils.	API GL-4/GL-5	ZF TE-ML 05B, 12L, 12N, 16F, 17B, 19C, 21B	DAF MAN 341 TYPE E3 MAN 341 TYPE Z2 MAN 342 TYPE M3 MAN M 3343 TYPE S JOHN DEERE JDM J11E JOHN DEERE JDM J11G SCANIA STO 1:0 ZF TE-ML 07

2_TRANSMISSION FLUIDS



TITAN

Gear Oils for Commercial Vehicles	Specifications	Approvals	FUCHS Recommendations
<p>TITAN CYTRAC 235.8 SAE 75W-90</p> <p>NEW</p>	<p>Premium Performance Gear Oil for highly-stressed hypoid axles in commercial vehicles formulated with fully-synthetic base oils. Developed for the longest oil change intervals especially in DAIMLER commercial vehicle axle drives.</p>	<p>API GL-4/GL-5</p> <p>MB-APPROVAL 235.8</p>	
<p>TITAN GEAR HYP LD SAE 80W-90</p>	<p>Super High Performance Gear Oil specially developed for Mercedes-Benz commercial vehicles. Offering enhanced thermal stability and fuel-economy potential.</p>	<p>API GL-5 API MT-1</p> <p>MAN 342 TYPE M3 MB-APPROVAL 235.20 ZF TE-ML 05A, 12L, 12M, 16B, 17B, 19B, 21A</p>	<p>MIL-PRF-2105 E ARVIN MERITOR AXLES MACK GO-J JOHN DEERE JDM J11E SCANIA STO 1:0 ZF TE-ML 07A</p>

2_TRANSMISSION FLUIDS



TITAN

Multifunctional Gear Oils for Construction Machinery	Specifications	Approvals	FUCHS Recommendations
TITAN UTTO PRO	Ultra High Performance Multifunctional Oil for gears, axles and hydraulic systems with improved wear protection and wide range of application temperatures.	API GL-4 SAE J 306: 75W-80	VOLVO WB 101 ALLISON C-4 CASE MS 1207/1209/1210 FORD M2C86-C FORD M2C134-D JOHN DEERE JDM J20C JOHN DEERE JDM J20D KOMATSU AXO 80 (KES 07.866) KUBOTA UDT FLUID MASSEY FERGUSON CMS M 1143, 1135 VOLVO WB 102 ZF TE-ML 03E, 03F, 05F, 06K
TITAN UTTO PLUS SAE 5W-30	Ultra High Performance Multifunctional Oil for gears, axles and hydraulic systems on construction and agricultural machinery with or without wet brakes and limited slip differentials.	SAE J300: 5W-30 SAE J306: 75W-80	CASE MS 1207/1209/1210 FORD M2C86-C, M2C134-D JOHN DEERE JDM J20C JOHN DEERE JDM J20D JOHN DEERE JDM J14 KOMATSU KES 07.866 KUBOTA UDT FLUID MASSEY FERGUSON CMS M 1143, 1135 STEYR 397.88.0001 VOLVO WB 101
TITAN UTTO ZF	Super High Performance Gear Oil for ZF axles with limited-slip differentials. Recommended for construction machinery and material-handling vehicles axles.		ZF TE-ML 05F, 06K, 17E, 21F KOMATSU-HANOMAG VOLVO WB 101 ZF TE-ML 03E
TITAN UTTO TO-4 SAE 10W	Super High Performance multifunctional lubricant for hydraulics in construction machinery.	API GL-4 CAT TO-4 KOMATSU KES 07.868.1	ALLISON C-4 DANA EATON
TITAN UTTO TO-4 SAE 30	Super High Performance multifunctional transmission lubricant for construction machinery.	API GL-4 CAT TO-4 KOMATSU KES 07.868.1	ZF TE-ML 03C, 07F ALLISON C-4 ALLISON TES-439 DANA EATON
TITAN UTTO TO-4 SAE 40	Super High Performance multifunctional transmission lubricant for construction machinery.	API GL-4 CAT TO-4 KOMATSU KES 07.868.1	ALLISON C-4 ALLISON TES-439 DANA EATON
TITAN UTTO TO-4 SAE 50	Super High Performance multifunctional lubricant for final drives in construction machinery.	API GL-4 CAT TO-4 KOMATSU KES 07.868.1	DANA EATON
TITAN UTTO TO-4 SAE 60	Super High Performance multifunctional lubricant for final drives in construction machinery.	API GL-4 CAT TO-4	

2_TRANSMISSION FLUIDS



TITAN

Double Clutch Transmission Fluid (DCTF)		Specifications	Approvals	FUCHS Recommendations
TITAN DCTF 52529 NEW	Premium Performance DCTF, specially developed for the Audi DL382 Double Clutch Transmission with wet clutch. Provides optimum wear protection and excellent friction properties even under hard conditions and offers best shifting performance over the whole lifetime.		VW TL 52 529-C	
TITAN DCTF	Premium Performance DCTF, specially developed for modern Double Clutch Transmission with wet clutch. The wide performance profile offers the use in diverse Double Clutch Transmissions of different manufacturers. Provide optimum wear protection and excellent shifting properties even under hard conditions over the whole lifetime.			BMW Drivelogic 7-speed CHRYSLER Powershift 6-speed FORD Powershift 6-speed MITSUBISHI TC-SST 6-speed PEUGEOT DCS 6-speed CITROEN DCS 6-speed RENAULT EDC 6-speed VOLVO Powershift 6-speed VW (AUDI, SEAT, SKODA) 6-speed FWD

Automatic Transmission Fluids (ATF)		Specifications	Approvals	FUCHS Recommendations
TITAN ATF 7134 FE	Premium Performance ATF with reduced viscosity, especially developed to further optimize fuel-economy and gearbox efficiency of latest generation Mercedes-Benz 7-speed automatic transmissions. Not downwards compatible with previous MB-ATF-Specifications. Product dyeing: blue.		MB-APPROVAL 236.15	
TITAN ATF 6000 SL	Premium Performance ATF offering maximum performance in passenger car applications such as automatic transmissions with torque converters or wet clutches as well as power steering systems. Formulation is licensed according to DEXRON VI and downwards compatible to any former DEXRON-specification. Product dyeing: red.		DEXRON VI VOITH H55.6335.xx ZF TE-ML 09	BMW 81 22 9 400 272 BMW 81 22 9 400 275 BMW 81 22 9 407 738 BMW 83 22 0 397 114 BMW 83 22 0 403 248 BMW 83 22 0 403 249 BMW 83 22 0 432 807 BMW 83 22 9 407 858 BMW 83 22 9 407 859
TITAN ATF 5005	Premium Performance ATF for automatic transmission in motor vehicles. Outstanding base oil quality for optimal cold temperature properties and high ageing stability. Durable friction properties for excellent wet clutch performance. Product dyeing: red.		MAN 339 TYPE V2 MAN 339 TYPE Z2 MB-APPROVAL 236.6 VOITH H55.6336.xx ZF TE-ML 04D, 14B, 16L, 17C	DEXRON III (H) ALLISON TES 295 ALLISON TES 389 BMW 81 22 9 400 272 BMW 81 22 9 400 275 BMW 83 22 0 403 248 BMW 83 22 9 407 738 BMW 83 22 9 407 807 BMW 83 22 9 407 858 BMW 83 22 9 407 859 FORD MERCON V MAN 339 TYPE Z3 OPEL 19 40 707 VOLVO 97341 VW TL 521 62 (G 052 162) ZF TE-ML 02F, 11B, 14C

2_TRANSMISSION FLUIDS



TITAN

Automatic Transmission Fluids (ATF)		Specifications	Approvals	FUCHS Recommendations
TITAN ATF 4400	Ultra High Performance ATF specifically formulated for Japanese passenger cars and light commercial vehicles. The high torque capacity exceeds the performance of many original fluids. Product dyeing: red.	JASO M315 TYPE 1A		DEXRON III AISIN WARNER/AW-1 BMW MINI 83 22 0 402 413 BMW MINI 83 22 7 542 290 CHRYSLER ATF +3/+4 DAEWOO DAIHATSU ALUMIX ATF MULTI FIAT TYPO T-IV FORD MERCON FORD M2C924-A/ M2C922-A1 GM 9986195 HONDA ATF Z-I HYUNDAI SP III, SP IV ISUZU BESCO ATF -II/ATF -III JATCO 3100 PL085/FWD (N402)/JF506E (K17) JWS 3309/TYPE T-IV KIA SP-IV MAZDA ATF D-III/ATF M-3 MITSUBISHI SP-II-III NISSAN MATIC C/D/J/S SAAB 3309 SUBARU ATF OIL/ATF OIL SPECIAL/ATF HP SUZUKI ATF 3309/3317 TOYOTA TYPE T/T-II/T-III/T-IV TOYOTA TYPE D-2/WS VW G 052 990/055 025
TITAN ATF 4134	Ultra High Performance ATF, specially developed to optimize shifting performance of Mercedes-Benz automatic transmissions. Product dyeing: red.		MB-APPROVAL 236.14 SSANG YONG (MB-automatic transmissions)	
TITAN ATF 4000	Ultra High Performance ATF for use in automatic transmissions as well as other ATF applications. Licensed according to DEXRON III (H). Improved low-temperature shifting compared to DEXRON II. Product dyeing: red.		ALLISON C-4 ALLISON TES-389 DEXRON III (H) MAN 339 TYPE V1 MAN 339 TYPE Z1 MB-APPROVAL 236.1 MB-APPROVAL 236.9 VOITH H55.6335.xx VOLVO 97341 ZF TE-ML 04D, 14A	BMW 81 22 9 400 272 BMW 81 22 9 400 275 BMW 81 22 9 407 738 BMW 83 22 0 403 248 BMW 83 22 9 407 765 BMW 83 22 9 407 807 BMW 83 22 9 407 858 BMW 83 22 9 407 859 CAT TO-2; FORD MERCON OPEL 19 40 707 / 767 VW TL 521 62 (G 052 162) ZF TE-ML 02F, 03D, 09, 11B, 17C

2_TRANSMISSION FLUIDS



TITAN

Automatic Transmission Fluids (ATF)		Specifications	Approvals	FUCHS Recommendations
TITAN ATF CVT	Ultra High Performance ATF specially designed for use in many CVT-gearboxes using push-belts or transmission chains made of steel. Product dyeing: none.		MB-APPROVAL 236.20 FORD WSS-M2C928-A	BMW 83 22 0 136 376 BMW 83 22 0 429 154 CHRYSLER CVTF+4 DAIHATSU AMIX CVTF-DC DODGE/JEEP NS-2/ CVTF+4 FORD WSS-M2C933-A GM DEX-CVT HONDA HCF-2 MITSUBISHI CVTF-J1 NISSAN NS-1/NS-2/NS-3 SUBARU Lineartronic CVTF/ECVT/iCVT SUZUKI TC/NS-2/CVT Green 1 TOYOTA TC/CVT FE VW TL 521 80 (G 052 180) VW TL 525 16 (G 052 516)
TITAN ATF 3353	Ultra High Performance DEXRON III-generation-ATF for automatic transmissions as well as any other ATF-applications. Developed for the MB automatic transmissions and transfer cases according manufacturer. Offers fuel-efficiency potential. Product dyeing: red.		MB-APPROVAL 236.12 VW TL 525 33 (G 052 533)	DEXRON III BMW 83 22 9 407 765 FORD M2C195-A FORD M2C202-B FORD M2C922-A1 SSANG YONG
TITAN ATF 3000	Super High Performance DEXRON II (D) ATF for automatic transmissions in commercial vehicles, machinery and passenger cars according to manufacturer's documentation. Product dyeing: red.		MAN 339 TYPE V1 MAN 339 TYPE Z1 MB-APPROVAL 236.1 VOITH H55.6335.xx ZF TE-ML 04D, 14A	DEXRON II (D) ALLISON C-4 BMW 81 22 9 400 272 BMW 81 22 9 400 275 BMW 81 22 9 407 738 CAT TO-2; FORD MERCON FORD M2C185-A FORD M2C138-CJ FORD M2C166-H FORD M2C9010-A OPEL 19 40 700 / 707 RENK-DOROMAT VOLVO; VW ZF TE-ML 02F, 03D, 09, 11A, 17C
TITAN ATF 10	High Performance ATF for transmissions, power steering systems and hydraulic drives which require a GM-specification TYPE A, Suffix A fluid. Product dyeing: red.		MB-APPROVAL 236.2	TASA MAN 339 TYPE A

3_HYDRAULIC FLUIDS



TITAN

Central Hydraulic / Power Steering Fluids		Specifications	Approvals	FUCHS Recommendations
TITAN ZH 4300 B	Premium Performance Central Hydraulic Oil formulated with fully-synthetic base oils. Product dyeing: green.		MAN M 3289	BMW 81 22 9 407 758 BMW 82 11 1 468 041 BMW 83 29 0 429 576 FENDT X 902 011 622 FORD M2C204-A OPEL 19 40 715 / -766 PORSCHE 000 043 203 33 PSA S712710 VOLVO 1161529 VW TL 521 46 (G 002 000)
TITAN ZH 5364 B	Premium Performance Central Hydraulic Oil approved by Mercedes-Benz for level control systems in passenger cars formulated with fully-synthetic base oils. Product dyeing: none.		MB-APPROVAL 344.0	
TITAN ZH 3044	Ultra High Performance power steering and central hydraulic oil for automotive applications. Product dyeing: green.		CHRYSLER MS-11655b VW TL 52519-B	AUDI/VW G 004 000 GMW 16613 LAND ROVER LR003401 OPEL 19 40 715 PORSCHE 000 043 206 56 SAAB 93160548 VOLVO 30741424
TITAN ZH LHM PLUS	Ultra High Performance Central Hydraulic Oil specially designed for the use in Citroën and Peugeot vehicles. Product dyeing: green.			ISO 7308 BMW 81 22 9 407 549 CASE FIAT 9.55597 IVECO 18-1823 MASSEY FERGUSON NH 610A PSA B71 2710 SDFG OF1611S
TITAN PSF	Super High Performance Power Steering Fluid approved by Mercedes-Benz for passenger cars and commercial vehicles. Product dyeing: none.		MB-APPROVAL 236.3	

Hydraulic Oils		Specifications	Approvals	FUCHS Recommendations
TITAN HYD MR 530 MC	Ultra High Performance multigrade hydraulic oil for construction machinery as well as diverse motor vehicle applications.	HVLPD covers SAE 5W to 30 or ISO VG 22-68 (100)		
TITAN HYD 1030	Super High Performance multigrade hydraulic oil for general machinery and motor vehicle applications.	HVLP according to DIN 51 524-3 HV according to ISO 11158	DENISON HF 0	CASE MS 1216

4_LUBRICANTS FOR AGRICULTURAL MACHINERY



AGRIFARM

AGRIFARM STOU Oils	Specifications	Approvals	FUCHS Recommendations
<p>AGRIFARM STOU MC PRO SAE 10W-40</p>	<p>Ultra High Performance Multifunctional Oil (STOU/MFO) of the latest generation for agricultural vehicles.</p>	<p>SAE J300: SAE 10W-40</p> <p>DEUTZ DQC III-10</p>	<p>ACEA E7(E5/E3),E4, API CI-4, API GL-3/GL-4/API GL-5 in tractors* MAN 3275 AFNOR NFE 48603 HV, ALLISON C-4 CASE MS 1207, 1209, 1210, 1230, CNH MAT 3505, 3509, 3525, 3526 DIN 51524-3: HVLP (-D) FNHA 2C-200.00, 201.00 FORD M2C48-C3, M2C86-B, M2C134-D, M2C159-B/C JOHN DEERE JDM J20C NEW HOLLAND 82009201/2/3 NH 030C, 330G, 330H, 410B, 420A, 526C MASSEY FERGUSON CMS M 1145, 1144, 1143, 1139, 1135 ZF TE-ML 06A, 06B, 06C, 06F, 06L, 07B * without HOLMER</p>
<p>AGRIFARM STOU MC SAE 10W-30</p>	<p>MC-synthesis Super High Performance Multifunctional Oil (STOU/MFO) for engines, manual gearboxes, wet brakes, hydraulics and turbo-drives in tractors and other agricultural machinery.</p>	<p>API CG-4 API GL-4 SAE J300: SAE 10W-30</p> <p>DEUTZ DQC I-02 ZF TE-ML 06B, 06F, 07B</p>	<p>AFNOR NFE 48603 HV DIN 51524-3: HVLP (-D) ACEA E3 ALLISON C-4 CASE MS 1207, 1209, 1210, 1230 CNH MAT 3505, 3509, 3525, 3526 FORD M2C48-C3, M2C86-B, M2C134-D, M2C159-B/C JOHN DEERE JDM J20 C NEW HOLLAND 82009201/2/3 NH 410B, 420A MASSEY FERGUSON CMS M 1145, 1144, 1143, 1139, 1135 SAE J306: SAE 75W-80 ZF TE-ML 06A, 06C</p>

4_LUBRICANTS FOR AGRICULTURAL MACHINERY



AGRIFARM STOU Oils	Specifications	Approvals	FUCHS Recommendations	
AGRIFARM STOU MC SAE 10W-40	Super High Performance Multifunctional Oil (STOU / MFO) based on MC-base-oil technology for engines, manual gearboxes, wet brakes, hydraulics and turbo-drives in tractors and other agricultural and other commercial vehicles.	API CG-4 API GL-4 SAE J300: SAE 10W-40	DEUTZ DQC I-02 FENDT KDM 41.2011 ZF TE-ML 06B, 06F, 07B	API GL-5 in tractors* ACEA E3 MAN 271 AFNOR NFE 48603 HV, ALLISON C-4 CASE MS 1207, 1209, 1210, 1230, CNH MAT 3505, 3509, 3525, 3526 DIN 51524-3: HVLP (-D) FORD M2C134-D, M2C159-B/C FNHA 2C-200.00, 201.00, FORD M2C48-C3, M2C-86 B JOHN DEERE JDM J20C NEW HOLLAND 82009201/2/3 NH 030C, 330G, 410B, 420A, 526C MASSEY FERGUSON CMS M 1145, 1144, 1143, 1139, 1135 SAE J306: SAE 75W-90 ZF TE-ML 06A, 06C, 06L * without HOLMER
AGRIFARM STOU SAE 15W-30	High Performance Multifunctional Oil (STOU / MFO) for engines, manual gearboxes, wet brakes, hydraulics in tractors and other agricultural equipment.	API CF-4 API GL-4		ACEA E2 CNH MAT 3525, 3526 DIN 51524 : HLP (-D) FNHA 200.00, 201.00 FORD M2C134-D, M2C159-B/C JOHN DEERE JDM J20C MASSEY FERGUSON CMS M 1145, 1144, 1143, 1139, 1135 NEW HOLLAND 82009201/2/3; NH 420A SDFG OU 1391, OT 1891 STEYR D-401 ZF TE-ML 06A, 06B, 06C, 07B
AGRIFARM STOU SAE 15W-40	High Performance Multifunctional Oil (STOU / MFO) for engines, manual gearboxes, wet brakes, hydraulics in tractors and other agricultural equipment.	API CF-4 API GL-4	FENDT KDM 41.2011	ACEA E2 CNH MAT 3525, 3526 DIN 51524 : HLP (-D) FNHA 200.00, 201.00 FORD M2C134-D, M2C159-B/C JOHN DEERE JDM J20C MASSEY FERGUSON CMS M 1145, 1144, 1143, 1139, 1135 NEW HOLLAND 82009201/2/3; NH 420A SDFG OU 1391, OT 1891 STEYR D-401 ZF TE-ML 06A, 06B, 06C, 07B

4_LUBRICANTS FOR AGRICULTURAL MACHINERY



AGRIFARM

AGRIFARM Engine Oils		Specifications	Approvals	FUCHS Recommendations
AGRIFARM MOT SAE 10W-40	Ultra High Performance Engine Oil of the latest conception of the SAE grade 10W-40. It was developed for advanced diesel engines which made high demands on service intervals and engine cleanliness. Specially recommended for normally aspirated and turbocharged engines.	ACEA E7 API CI-4 GLOBAL DHD-1 JASO DH-1		ALLISON C-4 CAT ECF-2 CUMMINS CES 20071/2/6/7/8 DAF DEUTZ DQC III MACK EO-M PLUS MAN M 3275-1 MTU DDC TYPE 2 RENAULT RLD / RLD-2 VOLVO VDS-3
AGRIFARM MOT SAE 15W-40	Super High Performance Engine Oil for normally aspirated and turbocharged diesel engines in tractors and other machinery which make high demands on service intervals and engine cleanliness.	ACEA E7 API CI-4 GLOBAL DHD-1 CAT ECF-1a/ECF-2	DEUTZ DQC III	ALLISON C-4 CAT TO-2 CASE MS 1121 CUMMINS CES 20071/2/6/7/8 DAF IVECO 18-1804 CLASSE T2 E7 MACK EO-M PLUS MAN M 3275-1 MTU DDC TYPE 2 NH 330H RENAULT RLD/RLD-2 STEYR A-201 VOLVO VDS-3

4_ LUBRICANTS FOR AGRICULTURAL MACHINERY



AGRIFARM

AGRIFARM UTTO Oils		Specifications	Approvals	FUCHS Recommendations
AGRIFARM UTTO MP	Super High Performance Multifunctional Oil (UTTO/MFO) for use in transmission and hydraulic systems with integrated wet brakes, clutches and differentials for agricultural and construction machinery.	API GL-4 SAE J300: 10W-30	ZF TE-ML 03E, 05F, 17E, 21F	AGCO Powerfluid 821 XL AGCO Q-186 (Whitefarm) ALLISON C-4 CASE MS 1230, 1210, 1209, 1207, 1206 CLAAS / LANDINI / SAME-Transmission CNH MAT 3505, 3506, 3509, 3525, 3526 FNHA-2-C-200.00 / -201.00 FORD M2C48-C3, ESN M2C86-B/C, M2C134-D JOHN DEERE JDM J20C KUBOTA UDT FLUID MASSEY FERGUSON CMS M 1145, 1143, 1141, 1135 NH 410B SAE J306: 75W-80 SDFG OT 1891 A VALTRA G02-08 ZF TE-ML 06K
AGRIFARM UTTO LN	Super High Performance Transmission-Hydraulic Fluid developed as a problem-solver for tractors in which conventional UTTO oils led to noisy wet brakes.	API GL-4 SAE J300: 20W-30		AGCO Powerfluid 821 XL AGCO Q-186 (Whitefarm) ALLISON C-4 CASE MS 1206, 1207, 1209, 1210, 1230 CNH MAT 3505, 3506, 3509, 3525, 3526 FNHA-2-C-200.00 / -201.00 FORD M2C48C3, ESN M2C86-B/C, M2C134-D JOHN DEERE JDM J20C MASSEY FERGUSON CMS M 1141, 1135 SAE J306: 80W-85 CLAAS / LANDINI / SAME-Transmission / DEUTZ-FAHR FENDT (non Vario)

4_LUBRICANTS FOR AGRICULTURAL MACHINERY



AGRIFARM

AGRIFARM Gear Oils		Specifications	Approvals	FUCHS Recommendations
AGRIFARM GEAR SAE 80W-90	Super High Performance Multigrade Gear Oil for synchromesh and non-synchromesh gearboxes as well as axles, power distributors, intermediary and auxiliary gearboxes in vehicles and machinery.	API GL-4/GL-5	ZF TE-ML 05A, 21A	MIL-L-2105 D NH 520A STEYR B-101
AGRIFARM GEAR SAE 85W-140	Super High Performance Multigrade Gear Oil for synchromesh and non-synchromesh gearboxes as well as axles, power distributors, intermediary and auxiliary gearboxes in vehicles and machinery.	API GL-4/GL-5	ZF TE-ML 05A, 21A	MIL-L-2105 D
AGRIFARM GEAR LS SAE 90	Super High Performance EP Gear Oil for axles fitted with limited-slip differentials in agricultural and other machinery.	API GL-5		NH 520B SDFG OP 1705LS VOLVO 97310 ZF TE-ML 05C, 12C, 16E

AGRIFARM Chain Saw Oil		Specifications	Approvals	FUCHS Recommendations
AGRIFARM CHAIN SAW OIL	Super High Performance Chain Saw Oil specially developed for all chain saws with pressurized chain oiling.			DOLMAR HUSQVARNA SOLO STIHL

AGRIFARM Milking Machine Oil		Specifications	Approvals	FUCHS Recommendations
AGRIFARM MILKING MACHINE OIL	Ultra High Performance Milking Machine Oil specially developed for use in the vacuum pumps of milking machines. It contains additives which protect against wear and corrosion and foaming. These features increase the functional reliability of such systems.			ALFA LAVAL WESTFALIA

5_MOTORCYCLE LUBRICANTS



Silkolene

RACE – For professional racers and everybody who rides at the limit		Specifications	Approvals	FUCHS Recommendations
SILKOLENE PRO R SAE 0W-20	Electrosyntec® -Technology Fully-synthetic four-stroke racing engine oil based on the latest Electrosyntec-Technology. Special racing formulation. Only for professional competition applications.			
SILKOLENE PRO 4 PLUS SAE 5W-40 SAE 10W-50	Electrosyntec® -Technology Four-stroke racing engine oil based on synthetic esters. Specially formulated for use in Superbikes, Supersports and production racers.	API SG/SH/SJ/SL	JASO MA2	
SILKOLENE PRO 4 SAE 10W-40 XP SAE 15W-50 XP SAE 10W-60 XP	Premium Performance Engine Oil	API SM/SN	JASO MA2	
SILKOLENE PRO KR2	Two-stroke race cart oil formulated with synthetic base oils and castor oil. Use manufacturer's recommended mixing ratios. Not miscible with other lubricants.		CIK-FIA	
SILKOLENE PRO 2	Electrosyntec® -Technology Fully-synthetic two-stroke racing engine oil. Specially formulated for extreme conditions. Not miscible with conventional two-stroke oils. Only suitable for Premix systems.		CIK-FIA	
SILKOLENE COMP 2 PLUS	Electrosyntec® -Technology Fully-synthetic two-stroke racing engine oil. Perfect for GP racing engines. Suitable for Premix and Autolube systems.	API TC JASO FC ISO-L-EGD		
SILKOLENE RSF 2.5/5/7.5/10/15	Fully-synthetic shock-absorber fluids and special fork oils with a high viscosity index. Specially developed for racing.			
SILKOLENE PRO CHAIN	Fully-synthetic racing chain lube spray for high-performance road, racing and motocross applications. For all chains with or without O-rings.			

5_MOTORCYCLE LUBRICANTS



Silkolene

RIDE – For the tourer and streetrider		Specifications	Approvals	FUCHS Recommendations
SILKOLENE COMP 4 SAE 10W-30 XP SAE 10W-40 XP SAE 15W-50 XP SAE 20W-50 XP	Ultra High Performance Engine Oil	API SL	JASO MA2	
SILKOLENE SUPER 4 SAE 15W-40	Four-stroke engine oil formulated with selected base oils. Specially for use in BMW motorcycles with and without wet clutches.	API SF/SG		BMW Motorrad JASO MA
SILKOLENE SUPER 4 SAE 10W-40	MC-synthesis four-stroke engine oil. High-quality standard product offering excellent protection.	API SF/SG/SH	JASO MA2	
SILKOLENE SUPER 4 SAE 20W-50	MC-synthesis four-stroke engine oil. High-quality standard product offering excellent protection.	API SF/SG	JASO MA2	
SILKOLENE V-TWIN SAE 20W-50	Mineral four-stroke engine oil. Specially developed for Harley-Davidson and European/Japanese Metric V-Twins.	API CF/SG/SH/SJ	JASO MA2	
SILKOLENE COMP 2	Electrosyntec® -Technology Synthetic two-stroke engine oil. Reliable protection against seizures, ring sticking and coking. Suitable for Premix and Autolube systems.	API TC JASO FC/FD ISO-L-EGD		

QUADS ATV – For professionals and fun bikers		Specifications	Approvals	FUCHS Recommendations
SILKOLENE QUAD ATV SAE 5W-40	Fully-synthetic four-stroke engine oil for highly-stressed Quads and ATVs. Offers first-class quality and reliable protection against wear.	API SG/SH/SJ/SL	JASO MA2	
SILKOLENE QUAD ATV SAE 10W-40	MC-synthesis four-stroke engine oil specially developed for Quads and ATVs. Standard, high-quality product for reliable protection.	API SG/SH/SJ	JASO MA2	

SCOOT – The name says it all		Specifications	Approvals	FUCHS Recommendations
SILKOLENE SCOOT 4 SAE 10W-40	Electrosyntec® -Technology Synthetic four-stroke engine oil for scooters and mopeds. Perfect for high-tech, four-stroke scooters.	API SG/SH/SJ	JASO MA2	
SILKOLENE SCOOT SPORT 2	Electrosyntec® -Technology Synthetic two-stroke engine oil for highly-stressed scooter engines. Suitable for Premix and Autolube systems.	API TC JASO FC/FD ISO-L-EGD		
SILKOLENE SCOOT 2	MC-synthesis two-stroke engine oil for scooters and mopeds. Suitable for Premix and Autolube systems.	API TC JASO FC		

5_MOTORCYCLE LUBRICANTS



Silkolene

MAINTAIN – Maintenance and protection for your bike	Specifications	Approvals	FUCHS Recommendations
SILKOLENE PRO SRG 75	Fully-synthetic, ester-based racing gear oil. Excellent protection against wear and easy shifting even at extreme temperatures.		
SILKOLENE COMP GEAR OIL SAE 80W-90	Synthetic, High Performance, ester-based gear oil. Particularly recommended when the gearbox contains aluminium components.	API GL-4/GL-3	
SILKOLENE BOA SAE 80W-90	High Performance gear oil for shaft drives and other hypoid, crown wheel and pinion applications.	API GL-5/GL-4	
SILKOLENE MAG COOL	Ready to use, powerful engine coolant for all year round use. Anti-cavitation performance exceeds that of conventional ethylene glycol based anti-freezes, providing the user with superior protection against engine and coolant pump damage due to this phenomenon.		
SILKOLENE SF 20 / 30 NEW	Fork oils for all types of motorcycle forks. Ensures smooth operation, optimum protection against wear and perfect road-holding.		
SILKOLENE FOAM FILTER OIL	Special product for the oiling of freshly-washed foam filters. Also available as a spray.		
SILKOLENE FOAM FILTER CLEANER	Special water-soluble cleaner used to wash foam filter elements.		
SILKOLENE TITANIUM DRI GEL	Advanced chain lubricating gel: Effectively resists fling-off and appears whitish when applied.		
SILKOLENE CHAIN LUBE	Synthetic chain lube spray for optimum wear and rust protection. For all motorcycle chains with or without O-rings.		
SILKOLENE BRAKE & CHAIN CLEANER	Highly effective cleaner for brakes and drive chains. Effectively removes caked residue.		
SILKOLENE CARB CLEANER	Carburettor cleaner spray.		
SILKOLENE PRO PREP	Special conditioning spray for plastics and painted surfaces restores the „brand-new“ look.		
SILKOLENE PRO WASH	Rapidly biodegradable, highly-effective motorcycle cleaner for all surfaces including aluminium. Available in 1-litre pump-bottles or in 25 litre drums.		
SILKOLENE ALL-IN-ONE	Multipurpose maintenance spray with a multitude of uses: SILKOLENE ALL-IN-ONE can be used to dry out damp ignitions or free rusted fasteners. It has excellent dewatering properties, repels moisture, penetrates corroded threads, lubricates and even offers protection against corrosion.		

5_ MOTORCYCLE LUBRICANTS



Silkolene

MAINTAIN – Maintenance and protection for your bike	Specifications	Approvals	FUCHS Recommendations
SILKOLENE SILKOPEN	A suspension of very fine lubricating graphite in a thin searching mineral oil carrier. SILKOLENE SILKOPEN penetrates corroded or seized threads, lubricates them at the same time to ease dismantling by lowering the torque required.		
SILKOLENE PRO BOOST	Octane improver to combat pre-ignition and improve acceleration.		

6_SERVICE PRODUCTS



MAINTAIN

Brake Fluids		Specifications	Approvals	FUCHS Recommendations
MAINTAIN DOT 5.1	Ultra High Performance Brake Fluid for hydraulic brake systems and clutch actuation in passenger cars, trucks and motorcycles.	FMVSS NR. 116 DOT 5.1 ISO 4925 CLASS 3/4/5.1 SAE J 1703/J 1704		
MAINTAIN DOT 4	Super High Performance Brake Fluid for hydraulic brake systems and clutch actuation in passenger cars, trucks and motorcycles.	FMVSS NR. 116 DOT 3/DOT 4 ISO 4925 CLASS 3/4 SAE J 1703/J 1704		FORD M6C62-A FORD M6C9103-A NH 800A OPEL 19 42 421

Antifreeze		Specifications	Approvals	FUCHS Recommendations
MAINTAIN FRICOFIN LL	Premium Performance Coolant Additive based on monoethylene glycol. Free from nitrite, amine, phosphate and silicates. Product dyeing: orange	ASTM D 3306 TYPE I BS 6580 FORD WSS-M97-B44-D JAGUAR/LAND-ROVER STJLR.651.5003 FVV Heft R443 KSM 2142 UNE 26-361-88/1	Bez.Reg.Arnsgb. E62.12.22.64-2011-1 DAF 74002 DEUTZ DQC CB-14 MAN 324 TYPE SNF MB-APPROVAL 325.3 MWM TR 0199-99-2091	AFNOR NFR 15-601 TYPE I ASTM D 4985 SAE J1034 CHRYSLER MS 12106 CNH MAT 3624 CUMMINS (ISBe engines at DAF and Leyland) DETROIT DIESEL 93K217 FIAT 9.55523 GM 6277M HYUNDAI MS 591-08 JASO M325 JIS K2234 KOMATSU AF-NAC (ready mix) LIEBHERR MD 1-36-130 NATO S-759 PSA B 71 5110 RENAULT TYPE D TOYOTA TSK 2601G-8A VW TL 774 D/F (different colour) VOLVO 128 6083/002 (=VOLVO TRUCKS, VOLVO CE, from MY 2005)
MAINTAIN FRICOFIN V	Ultra High Performance Coolant Additive based on Monoethyleneglycol. Free of nitrites, amines and phosphates. Product dyeing: pink-violet.		VW TL 774 J (G13)	
MAINTAIN FRICOFIN DP	Ultra High Performance Coolant Additive based on monoethylene glycol. Free from nitrite, amine and phosphate. Product dyeing: pink-violet.	AFNOR NF R 15-601 TYPE 1 ASTM D 3306 TYPE I ASTM D 4985 BS 6580 CUMMINS CES 14603	DEUTZ DQC CC-14 MAN 324 TYPE Si-OAT MB-APPROVAL 325.5 MB-APPROVAL 325.6	SCANIA TB 1451 VW TL 774-G
MAINTAIN FRICOFIN DP -35 NEW	Ultra High Performance Coolant Ready-Mix based on monoethylene glycol. Offers frost protection down to -35°C. Free from nitrite, amine and phosphate. Product dyeing: pink-violet	AFNOR NF R 15-601 TYPE 3 ASTM D 3306 TYPE III ASTM D 4985 BS 6580 CUMMINS CES 14603	DEUTZ DQC CC-14 MB-APPROVAL 326.5 MB-APPROVAL 326.6	MAN 324 TYPE Si-OAT SCANIA TB 1451 VW TL 774-G

6 SERVICE PRODUCTS



MAINTAIN

Antifreeze		Specifications	Approvals	FUCHS Recommendations
MAINTAIN FRICOFIN HDD	Ultra High Performance Engine Coolant concentrate based on monoethylene glycol. Free of amines and phosphates with low silicate technology. Product dyeing: yellow.	ASTM D 3306 TYPE I ASTM D 4985 ASTM D 6210 TYPE I-FF ASTM D 7583 AS/NZS 2008:2004 TYPE A BS 6580 CHRYSLER MS 7170 CHRYSLER MS 9769 DETROIT DIESEL 7SE298 FORD ESE-M97B44-A FORD ESE-M97B18-C FORD WSS M97B51-A1 GM 1825M & GM 1899M JIS K2234 MACK 014GS17004	MTU MTL 5048	CASE MS 1710 CAT EC-1 CUMMINS CES 14603 DETROIT DIESEL 93K217 (NOAT) FREIGHTLINER 48-2288D IVECO 18-1830 KENWORTH R026-170-97 MAN 324 TYPE N NEW HOLLAND WSN-M97B18-D PACCAR CS 0185 TOYOTA Motor Corp. RP 329
MAINTAIN FRICOFIN	Super High Performance Coolant Additive based on monoethylene glycol. Free from nitrite, amine and phosphate. Product dyeing: blue-green.	AFNOR NF R 15-601 TYPE 1 ASTM D 3306 TYPE I ASTM D 4985 BS 6580:1992 BUNDESWEHR TL 6805-0038/1 SAE J1034	BMW GS 94000 (BMW N 600 69.0) DEUTZ DQC CA-14 JENBACHER TA 1000-0201 MAN 324 TYPE NF MAN 324 TYPE NF PRITARDER MB-APPROVAL 325.0 MTU MTL 5048 MWM TR 0199-99-2091 PN-C 40007:2000 VOITH TURBO 172.00225010	DAF 74001 LIEBHERR TLV 035/TLV 23009 A OPEL/GM B 040 0240 VW TL 774-C (G 11)
MAINTAIN FRICOFIN -35	Super High Performance Coolant Ready-Mix based on monoethylene glycol. Offers frost protection down to -35°C. Free from nitrite, amine and phosphate. Product dyeing: green.	AFNOR NF R 15-601 TYPE 3 ASTM D 3306 TYPE III ASTM D 4985 BS 6580:1992	DEUTZ DQC CA-14 MB-APPROVAL 326.0	BMW GS 94000 (BMW N 600 69.0) DAF 74001 JENBACHER TA 1000-0201 LIEBHERR TLV 035/TLV 23009 A MAN 324 TYPE NF MAN 324 TYPE NF PRITARDER MTU MTL 5048 MWM TR 0199-99-2091 OPEL/GM B 040 0240 PN-C 40007:2000 VOITH TURBO 172.00225010 VW TL 774-C (G 11)
MAINTAIN FRICOFIN S	High Performance Coolant Additive based on monoethylene glycol. Free from nitrite, amine and phosphate. Product dyeing: light green.	ASTM D 3306 TYPE I BS 6580:1992		

6_SERVICE PRODUCTS



MAINTAIN

Washer Fluid Additive		Specifications	Approvals	FUCHS Recommendations
MAINTAIN CLEAN SCREEN	All season windscreen washer fluid additive with cleaning and antifreeze properties. Suitable for use with any type of washer nozzle and polycarbonate screens.			

Diesel Fuel Additives		Specifications	Approvals	FUCHS Recommendations
MAINTAIN DIESEL EFFECT	Super High Performance Fuel Additive improving diesel fuel properties for singular as well as constant treatment.			
MAINTAIN GASOLINE PLUS	High Performance Gasoline Additive Concentrate designed to clean the entire fuel system. Recommended for constant use.			
MAINTAIN WINTERFIT	Super High Performance Diesel Fuel and Heating Oil additive to prevent waxing and plugging at low temperatures.			

7_SPECIALTIES



Specialties – Oil Binder		Specifications	Approvals	FUCHS Recommendations
MAINTAIN ABSORPEX	Oil Binder Type III R, chemical binder	Reported by Hygiene Institut Gelsenkirchen MPL		

Specialties - Corrosion Protection Aerosols		Specifications	Approvals	FUCHS Recommendations
ANTICORIT DFG SPRAY	Spray and penetrating oil with MoS ₂ solid lubricants. Available as an aerosol spray.			
ANTICORIT 5F SPRAY	Surface protection spray. Available as an aerosol spray.			
ANTICORIT OHK SPRAY	Contact and engine protection spray. Excellent rust protection and good lubricants properties. Can be used as a contact spray. Available as an aerosol spray.			
ANTICORIT BW 366 SPRAY	Corrosion preventive wax spray with effective barrier function. Underfloor and cavity protection.			
ANTICORIT SYNTH SPRAY	Fully-synthetic corrosion dissolving spray with excellent penetrating effect.			
ANTICORIT CPX SPRAY	High Performance corrosion preventive for cavity protection and severe conditions. Also available as an aerosol spray.			
ANTICORIT BW 10 SPRAY	Corrosion preventive wax for protection of moulds, outdoor vehicles, press tools during long term downtimes.			

Specialties – Fitting Products		Specifications	Approvals	FUCHS Recommendations
RENAX GLEITSPRAY	Fitting product. Spray grease for hinges, joints and diverse movable small lubrication applications.			
RENOLIT SI 300 M	Low temperature silicon grease for plastic lubrication and mounting aid of o-rings and sealings.	MSI 2 P-70	VW TL 767 X DBL 6812.10	
RENOLIT CHUCK PASTE	White special paste for the lubrication of threads, screws and chucks, avoids fretting corrosion, NLGI 2-3.			
RENOLIT GL 1	Fitting product. Spray grease for hinges, joints and diverse movable small lubrication applications.			

Specialties – Cleaner		Specifications	Approvals	FUCHS Recommendations
FUCHS MULTICLEAN	Well-proven cleaner for multi purpose application in industries and workshops. Rapidly dislodges oil residues.			

8_GREASES



RENOLIT

Greases		Specifications	Approvals	FUCHS Recommendations
RENOLIT MP	Standard, multipurpose EP grease. Suitable for low temperatures. -40 °C to +120 °C.	KP 2 K-40 ISO-L-X-DCEB 2	MB-APPROVAL 267.0	
RENOLIT MP PLUS Only available for use in FUCHS system grease guns.	High Performance, multipurpose EP grease for plain and roller bearings with excellent adhesion, optimum corrosion protection and very good ageing stability, -30 °C to +120 °C.	KP 2 K-30 ISO-L-X-CCEB 2		
RENOLIT MP 150	Lithium thickened special grease with high ageing resistance, good EP and low temperature properties, temperature range from -40 °C up to +120 °C.	KP 2 K-40 ISO-L-X-DCEB 2	MB-APPROVAL 267.1	
RENOLIT MP 735	High Performance, multipurpose EP wheel bearing grease. NLGI grade 2, -40 °C to +120 °C.	KP 2 K-40 ISO-L-X-DCEB 2	MAN 283 Li-P 2 VW TL 735 STABILUS 100 15883	
RENOLIT LZR 2 H	Highly adhesive, Premium Performance-quality, long-life EP grease based on lithium soap for all plain and roller bearings as well as central lubrication systems in commercial vehicles and general machinery. Excellent corrosion protection even in the presence of saltwater, -30 °C to +140 °C.	KP 2 N-30 ISO-L-X-CDIB 2	Central lubrication system of BAIER & KÖPPEL LINCOLN and SKF Lubrication Solutions	
RENOLIT LZR 000	Semi-fluid grease for engine vehicle central lubrication systems. Gear grease for gearboxes in municipal machinery. Observe manufacturer's recommendations, -40 °C to +110 °C.	ISO-L-X-DBIB 00-000 GP 00-000 G-40	MAN 283 Li-P 00/000 MB-APPROVAL 264.0 SCHAEFFLER Commercial central lubrication system of LINCOLN and SKF Lubrication Solutions (for trucks)	
RENOLIT FLM 2 Also available for use in FUCHS system grease guns. Also in NLGI grade 0 available.	Universal, High Performance grease with solid lubricant additives with excellent wear protection. For the lubrication of commercial vehicles and machinery. Proven under extreme conditions such as in construction machinery, -30 °C to +140 °C.	KPF 2 N-30 ISO-L-X-CDEB 2	MAN 285 Li-PF 2	
RENOLIT RENOLIT LX-OTP 2	Fully synthetic special grease based on lithium complex thickener, containing solid lubricants, -40 °C to +160 °C.		MAN TUC 8080/00	

8 GREASES







RENOLIT

Specialties – Greases		Specifications	Approvals	FUCHS Recommendations
RENOLIT CA-LZ Also available in spray cans as RENOLIT UNIMAX LZ .	Long-term, tacky grease based on a special calcium soap with excellent water resistance, for the lubrication of construction and agricultural machinery, -30°C to +120°C, NLGI 2.	KP 2 K-30 ISO-L-X-CCHB 2		
RENOLIT CX-HT 2 Also available for use in FUCHS system grease guns . Also in NLGI grade 0 available.	Special calcium complex soap-based grease containing MoS ₂ and graphite for the lubrication of highly-stressed plain bearings at high temperatures. Excellent protection against corrosion and wear. Recommended for the greasing of gear wheels, -20 °C to +200 °C, NLGI grade 2, also available in spray can as RENOLIT UNILOAD .			
RENOLIT POLAR BLACK	Fully synthetic special grease based on lithium soap for the lubrication of high loaded plain and roller bearings. All-season grease for construction and mining machines.			
RENOLIT DURAPLEX EP 2 Also available for use in FUCHS system grease guns . Also in NLGI grade 1 and 3 available.	Special grease for the long-term lubrication of plain and roller bearings, such as vehicle clutch-release bearings, highly-stressed construction machinery bearings, etc., -30 °C to +160 °C.	KP 2 P-30 ISO-L-X-CEHB 2		
RENOLIT LX-PEP 2 Also in NLGI grade 1-2 and 3 available.	Special grease based on lithium complex soaps for long-life applications. Good corrosion protection, thermally and mechanically stable, specially suitable for wheel bearings of cars and trucks, -30 °C to +150 °C.	KP 2 N-30 ISO-L-X-CDEB 2	MAN 284 Li-H 2 MB-APPROVAL 265.1 SCHAEFFLER DB-Kenndatenblatt 873 499 ZF TE-ML 12 VW TL 52147X INTERPRECISE	

9_RAPIDLY BIODEGRADABLE LUBRICANTS



PLANTO

PLANTO Lubricants		Specifications	Approvals	FUCHS Recommendations	
PLANTO MOT SAE 5W-40		Super High Performance SAE 5W-40 Diesel Engine Oil. Rapidly biodegradable and specially recommended for use with alternative Diesel fuels.		ACEA E3/B3 API CG-4 KUBOTA SISU ZETOR	
PLANTOSYN 3268		Environmentally friendly, HVI multigrade hydraulic oil with high temperature stability based on fully-saturated, synthetic esters (HEES), rapidly biodegradable according to OECD 301 B >60%. Awarded the European Eco Label.	ISO 15380: HEES DIN 51524-3: HVLP DIN 51519: ISO VG 46	FENDT O&K BAUMASCHINEN ECO-Label	BOSCH REXROTH AG CAT BF-1 KRAMER ALLRAD PALFINGER SAUER DANFOSS TIMBERJACK VALMET / KOMATSU FOREST PONSSE
PLANTOSYN 3268 ECO		Environmentally friendly, HVI multigrade hydraulic fluid based on partly saturated synthetic esters (HEES), universally applicable, rapidly biodegradable according to OECD 301 B >60%, awarded with the European Eco Label.	DIN 51519: ISO VG 46 ISO 3448: ISO VG 46 DIN 51524-2: HLP DIN 51524-3: HVLP ISO 15380: HEES FENDT: KDM 28/2006	FENDT KDM 28/2006 ECO-Label	
PLANTOHYD 40 N		Environmentally compatible hydraulic and lubricating oils based on natural raw materials with additives to improve oxidation stability and ageing stability. Type HETG acc. to ISO 15380, for mobile and stationary hydraulic equipment. Rapidly biodegradable acc. to OECD 301 B >60%, awarded with the European Eco Label.	ISO 15380: HETG	ECO-Label	
PLANTO HYTRAC PLUS		Biodegradable Super High Performance Multifunctional Oil (UTTO) for tractor gearboxes with or without wet brakes.	SAE 10W-30 SAE 80		Several makes of tractors
PLANTOLUBE KS 32-N		Biodegradable rapeseed oil-based tacky lubricant for chains and other total-loss applications.			
PLANTO TAC 68		Biodegradable Super High Performance Chain Saw Oil based on rapeseed. For professional use in chain saws. Excellent lubricity and good ageing stability. Awarded the European Eco Label.		KWF ECO-Label	DOLMAR HUSQVARNA SOLO STIHL

9_RAPIDLY BIODEGRADABLE LUBRICANTS



PLANTO


PLANTO Lubricants		Specifications	Approvals	FUCHS Recommendations
PLANTOGEL 2 FS	Rapidly biodegradable EP grease with graphite additives, -30 °C to +120 °C.	KPFE 2 K-30 ISO-L-X-CCEB 2 DEMATIC RWE		
PLANTOGEL 000 S	Rapidly biodegradable semi-fluid EP grease for central lubrication systems of motor vehicles, industrial machinery and machine tools. Gear grease for gearboxes also in municipal machinery. Observe manufacturer's recommendations, -40 °C to +120 °C.	GPE 00-000 K-40 ISO-L-X-DCEB 00-000	MAN 283 Li-P 00/000 SKF Lubrication Solutions VOLVO	
PLANTOGEL ECO 2 N	Environmentally compatible, rapidly biodegradable total loss lubricating grease based on calcium soap and rape seed oil. Awarded with the EU-Ecolabel, temperature range -20 °C up to +70 °C.		ECO-Label	
PLANTOGEL ECO 2 S	Environmentally compatible, rapidly biodegradable EP-grease based on lithium soap and synthetic esters for the lubrication of plain and roller bearings. Good pumpability in central lubrication systems, awarded with the EU-Ecolabel, temperature range -40 °C up to +120 °C.		ECO-Label	

PRODUCT BROCHURES AUTOMOTIVE


Request under: export@fuchs-schmierstoffe.de




Image Flyer




Flyer
TITAN XTL



Flyer
Motor oils for
passenger cars



Flyer
Gear oils



Flyer
Automatic transmission
fluids



Flyer
MAINTAIN




Brochure
XTL for commercial vehicles



Brochure
PLANTO




Brochure
PRO GAS



Brochure
Lubricants for
Construction Companies



Brochure
Lubricants for
Transport Companies



Brochure
Gas engine oils



Flyer
Gas engine oils



Brochure
AGRIFARM



Flyer
AGRIFARM



XTL-Video
for passenger cars



XTL-Video
for commercial vehicles

The information contained in this product information is based on the experience and know-how of FUCHS SCHMIERSTOFFE GMBH in the development and manufacturing of lubricants and represents the current state-of-the-art. The performance of our products can be influenced by a series of factors, especially the specific use, the method of application, the operational environment, component pre-treatment, possible external contamination, etc. For this reason, universally-valid statements about the function of our products are not possible. The information given in this product information represents general, non-binding guidelines. No warranty expressed or implied is given concerning the properties of the product or its suitability for any given application. We therefore recommend that you consult a FUCHS SCHMIERSTOFFE GMBH application engineer to discuss application conditions and the performance criteria of the products before the product is used. It is the responsibility of the user to test the functional suitability of the product and to use it with the corresponding care. Our products undergo continuous improvement. We therefore retain the right to change our product program, the products, and their manufacturing processes as well as all details of our product information sheets at any time and without warning, unless otherwise provided in customer-specific agreements. With the publication of this product information, all previous editions cease to be valid.

Any form of reproduction requires express prior written permission from FUCHS SCHMIERSTOFFE GMBH.

© FUCHS SCHMIERSTOFFE GMBH. All rights reserved. Edition 06/2015

Contact:



FUCHS SCHMIERSTOFFE GMBH

Friesenheimer Straße 19
68169 Mannheim / Germany
Phone: 0621 3701-0
Fax: 0621 3701-570
E-mail: zentrale@fuchs-schmierstoffe.de
www.fuchs-schmierstoffe.de

Export Division
Friesenheimer Straße 19
68169 Mannheim / Germany
Phone: +49 621 3701-1703
Fax: +49 621 3701-7719
E-mail: export@fuchs-schmierstoffe.de
www.fuchs-schmierstoffe.com